

Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

edding refill ink whiteboard marker BT30, BTK25 (red) contained in: edding 28, edding 29

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Refilling ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

+49 (0) 41 02 / 80 8-0 Telephone no.

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319 Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

<u>Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)</u>

Hazard pictograms







Signal word Danger

Hazard statements

H225 H319 Highly flammable liquid and vapour. Causes serious eye irritation.



Trade name: edding refill ink whiteboard marker BT30, BTK25 (red) contained in: edding 28, edding 29

Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 for extinction. P501 Dispose of contents/container in accordance with local and national regulations.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

No	Substance name	ubstance name Additional information				
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	entration		%
	REACH no					
1	ethanol		pls. r	efer to footnote	(1)	
	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>=	50.00 - <	100.00	%-b.w.
2	1-methoxy-2-propa	nol				
	107-98-2 203-539-1 603-064-00-3	Flam. Liq. 3; H226 STOT SE 3; H336	>=	10.00 - <	25.00	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

⁽¹⁾ Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	ethanol	64-17-5		200-578-6	
	List of approved workplace exposure limits (WELs) / E	EH40			
	Ethanol				
	TWA	1920	mg/m³	1000	ml/m³
2	1-methoxy-2-propanol	107-98-2		203-539-1	
	2000/39/EWG				
	1-Methoxypropanol-2				
	STEL	568	mg/m³	150	ml/m³
	TWA	375	mg/m³	100	ml/m³
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / E	EH40			
	1-Methoxypropan-2-ol				
	STEL	560	mg/m³	150	ml/m³
	TWA	375	mg/m³	100	ml/m³
	Skin resorption / sensibilisation	Sk		•	

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 9: Physical and chemical properties

9.1	Information on	basic ph	vsical and	chemical	properties
-----	----------------	----------	------------	----------	------------

Form/Colour			
liquid			
red			
Odour			
characteristic			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
Value		78	°C
Melting point / melting range			
No data available			
Decomposition point / decomposition rang	je		
No data available			
Flash point			
Value		13	°C
Ignition temperature			
Value		287	°C
Auto-ignition temperature			
Remarks	Product is not self	figniting.	
Oxidising properties			
No data available			
Explosive properties			
This product is not explosive. In and after use	danger of production	of inflam	mable compounds.
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
Value		1.7	% vol
Upper flammability or explosive limits			
Value		15.0	% vol
Vapour pressure			
Value		59	hPa
Reference temperature		20	°C
Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			
			· · · · · · · · · · · · · · · · · · ·
no data available			
no data available Solubility in water Remarks			



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Solubility(ies)		
No data available		
Partition coefficient: n-octanol/water		
No data available		
Viscosity		
No data available		
Solvent content		
Value	79.1	%

9.2 Other information

Other info	rmation	
No data ava	vailable.	

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity						
No	Substance name	CAS	no.	EC no.			
1	1-methoxy-2-propanol	107-	98-2	203-539-1			
LD5	0		5660	mg/kg bodyweigh			
Species		rat					
Sou	rce	Manufacturer					

Acu	Acute dermal toxicity						
No	Substance name	CAS no.		EC no.			
1	1-methoxy-2-propanol	107-98-2	2	203-539-1			
LD5	0		9999.99	mg/kg bodyweight			
Spec	cies	rabbit					
Soul	rce	Manufacturer					



Trade name: edding refill ink whiteboard marker BT30, BTK25 (red) contained in: edding 28, edding 29

Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.



Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3 Classification code F1 Packing group Ш Hazard identification no. 33 **UN** number UN1263 Technical name **PAINT** Special Provision 640 640D Tunnel restriction code D/E Label

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT
EmS F-E+S-E
Label 3

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe No 3, 40 XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances				
This product is subject to Part I of Annex I, risk category:	P5b			



Trade name: edding refill ink whiteboard marker BT30, BTK25 (red) contained in: edding 28, edding 29

Current version: 5.0.0, issued: 30.06.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO Umwelt Consult GmbH.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

edding refill ink whiteboard marker BT30, BTK25 (black) contained in: edding 28, edding 29

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Refilling ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

+49 (0) 41 02 / 80 8-0 Telephone no.

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319 Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

<u>Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)</u>

Hazard pictograms







Signal word

Danger

Hazard statements

H225 H319 Highly flammable liquid and vapour. Causes serious eye irritation.



Trade name: edding refill ink whiteboard marker BT30, BTK25 (black) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 for extinction.
P501 Dispose of contents/container in accordance with local and national regulations.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

No	Substance name		Addit	ional information	n	
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	entration		%
	REACH no					
1	ethanol		pls. re	efer to footnote	(1)	
	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>=	50.00 - <	100.00	%-b.w.
2	1-methoxy-2-propa	nol				
	107-98-2 203-539-1 603-064-00-3	Flam. Liq. 3; H226 STOT SE 3; H336	>=	10.00 - <	25.00	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

⁽¹⁾ Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.				
1	ethanol	64-17-5		200-578-6				
	List of approved workplace exposure limits (WELs) / EH40							
	Ethanol							
	TWA	1920	mg/m³	1000	ml/m³			
2	1-methoxy-2-propanol	107-98-2		203-539-1				
	2000/39/EWG							
	1-Methoxypropanol-2							
	STEL	568	mg/m³	150	ml/m³			
	TWA	375	mg/m³	100	ml/m³			
	Skin resorption / sensibilisation	Skin						
	List of approved workplace exposure limits (WELs) / I	EH40						
	1-Methoxypropan-2-ol							
	STEL	560	mg/m³	150	ml/m³			
	TWA	375	mg/m³	100	ml/m³			
	Skin resorption / sensibilisation	Sk	<u> </u>					

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product . Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

SECTION 9: Physical and chemical properties

				4.
9.1	Information on	basic physical and	chemical	properties

Form/Colour			
liquid			
black			
Odour			
characteristic			
Odour threshold			
No data available			
pH value not determined			
Boiling point / boiling range Value	T	78	°C
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value		13	°C
Ignition temperature			
Value		287	°C
Auto-ignition temperature			
Remarks	Product is not selfi	gniting.	
Oxidising properties			
No data available			
Explosive properties This product is not explosive. In and after use da	anger of production of	f inflamn	nable compounds
	ariger or production c	i iiiiiaiiii	nable compounds.
Flammability (solid, gas) No data available			
Lower flammability or explosive limits			
Value		1.7	% vol
Upper flammability or explosive limits			
Value Value		15.0	% vol
Vapour pressure			
Value		59	hPa
Reference temperature		20	°C
Vapour density			
No data available			
Evaporation rate No data available			
Relative density No data available			
Density			
No data available			
Solubility in water			
Remarks	partially miscible		



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

Solubility(ies)						
No data available						
Partition coefficient: n-octanol/water	Partition coefficient: n-octanol/water					
No data available	No data available					
Viscosity						
No data available						
Solvent content						
Value	79.1	%				

9.2 Other information

Other info	rmation	
No data ava	vailable.	

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity						
No	Substance name	CAS	no.	EC no.			
1	1-methoxy-2-propanol	107-9	98-2	203-539-1			
LD5	0		5660	mg/kg bodyweight			
Species		rat					
i ·		Manufacturer					

Acu	Acute dermal toxicity							
No	Substance name	CAS no.		EC no.				
1	1-methoxy-2-propanol	107-98-2	2	203-539-1				
LD5	0		9999.99	mg/kg bodyweight				
Spec	cies	rabbit						
Soul	rce	Manufacturer						



Trade name: edding refill ink whiteboard marker BT30, BTK25 (black) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.



Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3 Classification code F1 Packing group Ш Hazard identification no. 33 **UN** number UN1263 Technical name **PAINT** Special Provision 640 640D Tunnel restriction code D/E Label

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT
EmS F-E+S-E
Label 3

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe No 3, 40 XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous s	substances
This product is subject to Part I of Annex I, risk category:	P5b



Trade name: edding refill ink whiteboard marker BT30, BTK25 (black) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 30.06.2015 Replaced version: 5.0.0, issued: 10.09.2014 Region: GB

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO Umwelt Consult GmbH.



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

edding refill ink whiteboard marker BT30, BTK25 (blue) contained in: edding 28, edding 29

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Eye Irrit. 2; H319

Flam. Liq. 2; H225

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

<u>Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)</u>

Hazard pictograms







Signal word Danger



Trade name: edding refill ink whiteboard marker BT30, BTK25 (blue) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Alcoholic solution of organic pigments, binding agents and additives.

Hazardous ingredients

	%
3.00	%-b.w.
5.00	%-b.w.
9.00	%-b.w.
	9.00

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. In case of persisting adverse effects consult a physician.

After skin contact

Wash immediately with plenty of water for several minutes. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Run-off water from fire fighting must not be discharged into drains or enter surface water. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

Do not store together with: Oxidizing agents; Alcali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.		
1	ethanol	64-17-5		200-578-6		
	List of approved workplace exposure limits (WELs) / EH40					
	Ethanol					
	TWA	1920	mg/m³	1000	ml/m³	
2	propan-2-ol	67-63-0		200-661-7		
	List of approved workplace exposure limits (WELs) / E	LU40				
	List of approved workplace exposure littles (WELS) / E	-Π 4 υ				
	Propan-2-ol	<u>-Π40</u>				
		1250	mg/m³	500	ml/m³	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name		CAS / EC no		
	Route of exposure	Exposure time	Effect	Value	
1	ethanol			64-17-5	
			<u> </u>	200-578-6	
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	systemic	950	mg/m³
	inhalative	Short term (acut)	local	1900	mg/m³
2	propan-2-ol			67-63-0	
				200-661-7	
	dermal	Long term (chronic)	systemic	888	mg/kg/day
	inhalative	Long term (chronic)	systemic	500	mg/m³
3	Bis(2-ethylhexyl) maleate			142-16-5	
				205-524-5	
	dermal	Long term (chronic)	local	3.91	mg/kg/day
	dermal	Long term (chronic)	systemic	0.42	mg/kg/day
	inhalative	Long term (chronic)	local	1.95	mg/m³
	inhalative	Long term (chronic)	systemic	1.95	mg/m³



Trade name: edding refill ink whiteboard marker BT30, BTK25 (blue) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethanol			64-17-5	
				200-578-6	
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Short term (acut)	local	950	mg/m³
	inhalative	Long term (chronic)	systemic	114	mg/m³
2	propan-2-ol			67-63-0	
				200-661-7	
	oral	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m³

PNEC values

No	Substance name		CAS / EC n	0
	ecological compartment	Туре	Value	
1	ethanol		64-17-5	
			200-578-6	
	water	fresh water	0.96	mg/l
	water	marine water	0.79	mg/l
	water	fresh water sediment	3.6	mg/kg
	with reference to: dry weight			
	water	Aqua intermittent	2.75	mg/l
	soil	-	0.63	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	580	mg/l
	secondary poisoning	-	0.72	g/kg
	with reference to: food			
2	propan-2-ol		67-63-0	
			200-661-7	
	water	fresh water	140.9	mg/l
	water	marine water	140.9	mg/l
	water	fresh water sediment	552	mg/l
	water	marine water sediment	552	mg/l
	water	Aqua intermittent	140.9	
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/l
	secondary poisoning	-	160	mg/kg
	with reference to: food			
3	Bis(2-ethylhexyl) maleate		142-16-5 205-524-5	
	water	fresh water	0.001	mg/l
	water	marine water	0.0001	mg/l
	water	fresh water sediment	15.95	mg/kg
	water	marine water sediment	1.595	mg/kg
	soil	-	3.19	mg/kg
	sewage treatment plant	-	100	mg/l

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, Filter A



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	•	0.5	mm
Breakthrough time	>=	8	h
Appropriate Material	Fluorocarbon rub	ber (Viton)	
Material thickness		0.4	mm
Breakthrough time	>=	8	h
Appropriate Material	Polychloroprene		
Material thickness		0.5	mm
Breakthrough time	>=	2	h

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour				
liquid				
blue				
Odour				
alkohol-like				
Odour threshold				
No data available				
pH value				
Value	3	-	9	
Boiling point / boiling range				
Value			78.3	°C
Melting point / melting range				
Value			-114.5	°C
Decomposition point / decomposition range				
No data available				
Flash point				
Value			12	°C
Auto-ignition temperature				
Value			425	°C



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

Oxidising properties No data available				
Explosive properties				
No data available				
Flammability (solid, gas)				
No data available				
Lower flammability or explosive limits				
Value		3.5	% vol	
Upper flammability or explosive limits				
Value		15.0	% vol	
Vapour pressure				
Value		59	hPa	
Reference temperature		20	°C	
Vapour density				
No data available				
Evaporation rate				
No data available				
Relative density				
No data available				
Density				
No data available				
Solubility in water	_			
Remarks	miscible			
Solubility(ies)				
No data available				
Partition coefficient: n-octanol/water				
No Substance name		CAS no.		EC no.

Part	Partition coefficient: n-octanol/water					
No	Substance name		CAS no.		EC no.	
1	propan-2-ol		67-63-0		200-661-7	
log F	Pow			0.05		
Refe	erence temperature			25	°C	
Soul	rce	ECHA				

Viscosity				
Value	7.5	- 12	cР	
Reference temperature		20	°C	
Туре	dynamic			

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

10.5 Incompatible materials

Oxidizing agents; Alkali metals; Earth alkali metals; Nitric acid; sulfuric acid; Peroxides

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity						
Substance name		CAS no.		EC no.		
ethanol		64-17-5		200-578-6		
)			10740	mg/kg bodyweight		
cies	rat					
od	OECD 401					
ce	ECHA					
propan-2-ol		67-63-0		200-661-7		
)			5840	mg/kg bodyweight		
cies	rat					
od	OECD 401					
ce	ECHA					
Bis(2-ethylhexyl) maleate		142-16-5		205-524-5		
)	>		2000	mg/kg bodyweight		
cies	rat					
od	OECD 401					
ce	ECHA					
	Substance name ethanol) cies nod ce propan-2-ol) cies nod ce Bis(2-ethylhexyl) maleate) cies nod	Substance name ethanol orat Disies rat Sided OECD 401 Disces rat Sided OECD 401 Ce ECHA Bis(2-ethylhexyl) maleate > Disces rat Sides rat Sides rat OCCD 401 OECD 401	Substance name CAS no. ethanol 64-17-5 objects rat open open open open open open open open	Substance name CAS no. ethanol 64-17-5 D 10740 cies rat odd OECD 401 cce ECHA propan-2-ol 67-63-0 D 5840 cies rat odd OECD 401 cce ECHA Bis(2-ethylhexyl) maleate 142-16-5 D > cies rat odd OECD 401		

Acu	Acute dermal toxicity					
No	Substance name		CAS no.		EC no.	
1	Bis(2-ethylhexyl) maleate		142-16-5		205-524-5	
LD5	0			14000	mg/kg bodyweight	
Spe	cies	rabbit			-	
Sou		ECHA				

Acu	te inhalational toxicity				
No	Substance name		CAS no.		EC no.
1	ethanol		64-17-5		200-578-6
LC5	0			124.7	mg/l
Dura	ation of exposure			4	h
State	e of aggregation	Dust/mist			
Spe	cies	rat			
Meth	nod	OECD 403			
Sou	rce	ECHA			
2	propan-2-ol		67-63-0		200-661-7
LC5	0	>		10000	ppmV
Dura	ation of exposure			6	h
State	e of aggregation	Gas			
Spe	cies	rat			
Meth	nod	OECD 403			
Sou	rce	ECHA			

Skin	Skin corrosion/irritation						
No	Substance name	CAS no.	EC no.				
1	propan-2-ol	67-63-0	200-661-7				
Spec	cies	rabbit					
Sour	ce	ECHA					
Eval	uation	non-irritant					



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

Seri	Serious eye damage/irritation						
No	Substance name	CAS no.	EC no.				
1	propan-2-ol	67-63-0	200-661-7				
Spe	cies	rabbit					
Meth	nod	OECD 405					
Sou	rce	ECHA					
Eval	uation	irritant					

Res	Respiratory or skin sensitisation					
No	Substance name	CAS no.	EC no.			
1	ethanol	64-17-5	200-578-6			
Rou	te of exposure	Skin				
Spe	cies	mouse				
Meth	nod	OECD 429				
Sou	rce	ECHA				
Eval	uation	non-sensitizing				
2	propan-2-ol	67-63-0	200-661-7			
Rou	te of exposure	Skin				
Spe	cies	guinea pig				
Method		OECD 406				
Source		ECHA				
Eval	uation	non-sensitizing				

Geri	Germ cell mutagenicity					
No	Substance name	CAS no.	EC no.			
1	ethanol	64-17-5	200-578-6			
Source		ECHA				
Eval	uation/classification	Based on available data, the classification	criteria are not met.			
2	propan-2-ol	67-63-0	200-661-7			
Source		ECHA				
Eval	Evaluation/classification Based on available data, the classification criteria are not met.					

Rep	Reproduction toxicity					
No	Substance name	CAS no.	EC no.			
1	ethanol	64-17-5	200-578-6			
Source		ECHA				
Evaluation/classification		Based on available data, the classification	n criteria are not met.			

Card	Carcinogenicity					
No	Substance name	CAS no.	EC no.			
1	ethanol	64-17-5	200-578-6			
Source		ECHA				
Evaluation/classification		Based on available data, the classification criteria are not met.				

STOT-single exposure	
No data available	

STOT-repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

Page 9 of 13



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Tox	Toxicity to fish (acute)					
No	Substance name	CAS no.	EC no.			
1	ethanol	64-17-5	200-578-6			
LC5	0	> 14	-000 mg/l			
Dura	ation of exposure	96	h h			
Species		Pimephales promelas				
Meth	nod	EPA E03-05				
Sou	rce	ECHA				
Eval	uation/classification	Based on available data, the class	ssification criteria are not met.			
2	propan-2-ol	67-63-0	200-661-7			
LC5	0	96	i40 mg/l			
Dura	ation of exposure	96	h h			
Species		Pimephales promelas				
Method		OECD 203				
Sou	rce	ECHA				

Toxi	city	to fis	sh (c	hronic)
------	------	--------	-------	---------

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

	or o						
Biod	Biodegradability						
No	Substance name	CAS no.		EC no.			
1	propan-2-ol	67-63-0		200-661-7			
Туре		BOD/COD					
Value			53	%			
Duration			5	day(s)			
Source		ECHA					
Evaluation		readily biodegradable					

12.3 Bioaccumulative potential

Part	Partition coefficient: n-octanol/water					
No	Substance name	CAS no.		EC no.		
1	propan-2-ol	67-63-0		200-661-7		
log F	Pow		0.05			
Reference temperature			25	°C		
		ECHA				



Trade name: edding refill ink whiteboard marker BT30, BTK25 (blue) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1263
Technical name PAINT
Danger releasing substance ethanol

bis (2-ethylhexyl) maleate n 640 640D

Special Provision 640
Tunnel restriction code
Label

540
D/E
D/E
3

Environmentally hazardous Symbol "fish and tree"

substance mark

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT
Danger releasing substance ethanol

bis (2-ethylhexyl) maleate

EmS F-E+S-E

Label 3

Marine pollutant mark Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3



Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe

No. 3, 40

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5b

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de



Trade name: edding refill ink whiteboard marker BT30, BTK25 (blue) contained in: edding 28, edding 29

Current version: 6.0.0, issued: 16.06.2017 Replaced version: 5.1.0, issued: 16.12.2015 Region: GB

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 24936



Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Refilling ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

+49 (0) 41 02 / 80 8-0 Telephone no.

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eve Dam. 1; H318 Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

<u>Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)</u>

Hazard pictograms



GHS02





Signal word

Danger

Hazardous component(s) to be indicated on label:

propan-1-ol



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Hazard statements

H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 for extinction.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

nazardous ingredients							
No	Substance name		Additional information				
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conc	Concentration		%	
	REACH no						
1	propan-1-ol						
	71-23-8	Eye Dam. 1; H318	>=	50.00 - <	100.00	%-b.w.	
	200-746-9	Flam. Liq. 2; H225					
	603-003-00-0	STOT SE 3; H336					
	-						
2	propan-2-ol						
	67-63-0	Eye Irrit. 2; H319	>=	2.50 - <=	10.00	%-b.w.	
	200-661-7	Flam. Liq. 2; H225					
	603-117-00-0	STOT SE 3; H336					
	-						
3	1-methoxy-2-propa	nol					
	107-98-2	Flam. Liq. 3; H226	>=	2.50 - <=	10.00	%-b.w.	
	203-539-1	STOT SE 3; H336					
	603-064-00-3						
	-						

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. Poisonous symptoms can first be observed after several hours, therefore medical observation for at least 48 hours is necessary.



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.



Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	propan-1-ol	71-23-8		200-746-9	
	List of approved workplace exposure limits (WELs) / E	H40			
	Propan-1-ol				
	STEL	625	mg/m³	250	ml/m³
	TWA	500	mg/m³	200	ml/m³
	Skin resorption / sensibilisation	Sk			
2	propan-2-ol	67-63-0		200-661-7	
	List of approved workplace exposure limits (WELs) / E	H40			
	Propan-2-ol				
	STEL	1250	mg/m³	500	ml/m³
	TWA	999	mg/m³	400	ml/m³
3	1-methoxy-2-propanol	107-98-2		203-539-1	
	2000/39/EWG				
	1-Methoxypropanol-2				
	STEL	568	mg/m³	150	ml/m³
	TWA	375	mg/m³	100	ml/m³
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / E	H40			
	1-Methoxypropan-2-ol				
	STEL	560	mg/m³	150	ml/m³
	TWA	375	mg/m³	100	ml/m³
	Skin resorption / sensibilisation	Sk			

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.



Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

.1 Information on basic physical and chemical properties					
Form/Colour					
liquid					
green					
Odour					
characteristic					
Odour threshold					
No data available					
pH value					
No data available					
Boiling point / boiling range	T.				
Value		82	°C		
Melting point / melting range					
No data available					
Decomposition point / decomposition range					
No data available					
Flash point					
Value		13	°C		
		10	<u> </u>		
Ignition temperature	ı	007	00		
Value		287	°C		
Auto-ignition temperature					
Remarks	Product is not selfi	gniting.			
Oxidising properties					
No data available					
Explosive properties					
This product is not explosive. In and after use da	nger of production o	f inflamn	nable compounds		
	rigor or production o	1 IIIII CITIII	iable compounds.		
Flammability (solid, gas)					
No data available					
Lower flammability or explosive limits					
Value		2.1	% vol		
Upper flammability or explosive limits					
Value		13.5	% vol		



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Vanaur program				
Vapour pressure Value		10	hDe	
		19 20	hPa °C	
Reference temperature		20	, ,	
Vapour density				
No data available				
Evaporation rate				
No data available				
Relative density				
No data available				
Density				
no data available				
Solubility in water				
Remarks	partially miscible)		
Solubility(ies)				
No data available				
				_
Partition coefficient: n-octanol/wat	er			
No data available				
Viscosity				
Value		11.5	mPa*s	
Reference temperature		20	°C	
Туре	dynamic			
Solvent content				
Value		81.3	%	
Solids content				
Value		6.5	%	
	•			

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity					
No	Substance name	CA	S no.		EC no.	
1	propan-1-ol	71-	23-8		200-746-9	
LD5	0		;	3000	mg/kg bodyweight	
Spe	cies	rat				
Sou	rce	Manufacturer				
2	propan-2-ol	67-	63-0		200-661-7	
LD5	0		;	5280	mg/kg bodyweight	
Spe	cies	rat				
Sou	rce	Manufacturer				
3	1-methoxy-2-propanol	107	7-98-2		203-539-1	
LD5	0		;	5660	mg/kg bodyweight	
Spe	cies	rat				
Sou	rce	Manufacturer				

Acu	te dermal toxicity				
No	Substance name		CAS no.		EC no.
1	propan-1-ol		71-23-8		200-746-9
LD5	0			4000	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			
2	propan-2-ol		67-63-0		200-661-7
LD5	0			12800	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			
3	1-methoxy-2-propanol		107-98-2		203-539-1
LD5	0			9999.99	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			

Acu	Acute inhalational toxicity					
No	Substance name		CAS no.		EC no.	
1	propan-1-ol		71-23-8		200-746-9	
LC5	0	>		33.8	mg/l	
Dura	ation of exposure			4	h	
State	e of aggregation	Vapour				
Spe	cies	rat				
Meth	nod	OECD 403				
Sou	ce	ECHA				
2	propan-2-ol		67-63-0		200-661-7	
LC5	0			72.6	mg/l	
Dura	ation of exposure			4	h	
State	e of aggregation	Vapour				
Spe	cies	rat				
Sou	ce	Manufacturer	•			



Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)					
No	Substance name	CAS no.		EC no.	
1	propan-2-ol	67-63-0		200-661-7	
LC5	0		9640	mg/l	
Dura	ation of exposure		96	h	
Spec	cies	Pimephales promelas			
Soul	rce	Manufacturer			

Toxicity to fish (chronic)

No data available

Toxi	Toxicity to Daphnia (acute)				
No	Substance name	CAS no.		EC no.	
1	propan-2-ol	67-63-0		200-661-7	
EC5	0		13299	mg/l	
Dura	ation of exposure		48	h	
Spec	cies	Daphnia magna			
Soul	rce	Manufacturer			

Toxicity to Daphnia (chronic)

No data available

Tox	city to algae (acute)			
No	Substance name	CAS no.		EC no.
1	propan-2-ol	67-63-0		200-661-7
EC5	0	>	1000	mg/l
Dura	ation of exposure		72	h
Spe	cies	Desmodesmus subspicatus		
Sou	rce	Manufacturer		



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biod	Biodegradability					
No	Substance name	CAS no.		EC no.		
1	propan-2-ol	67-63-0		200-661-7		
Valu	ie		95	%		
Dura	ation		21	day(s)		
Meth	nod	OECD 301 E				
Sou	rce	Manufacturer				
Eval	uation	readily biodegradable				

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other	information	Ī

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1263

Technical name PAINT RELATED MATERIAL

Special Provision 640 640D
Tunnel restriction code D/E
Label 3



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263

Proper shipping name PAINT RELATED MATERIAL

EmS F-E+S-E Label 3

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263

Proper shipping name Paint related material

Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe

No. 3, 40

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

P5b

15.2 Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.



Trade name: edding refill ink whiteboard marker BT30, BTK25 (green) contained in: edding 28, edding 29

Current version: 4.1.0, issued: 22.10.2015 Replaced version: 4.0.0, issued: 10.09.2014 Region: GB

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO Umwelt Consult GmbH.