

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2

Revision: 25.09.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU All purpose 20ml Bl. EN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.

   Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling: methyl acetate acetone

(Contd. on page 2)

- GB-EN

www.uhu.com 1/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

(Contd. of page 1)

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from open flames. - No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

#### 2.3 Other hazards

- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions. Adhesive

· Dangerous components:			
CAS: 79-20-9 methyl acetate	50-100%		
EINECS: 201-185-2 🗞 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319; STOT SE 3, H336			
CAS: 64-17-5 ethanol	2.5-10%		
EINECS: 200-578-6 🚸 Flam. Liq. 2, H225; 🕚 Eye Irrit. 2, H319			
CAS: 67-64-1 acetone	2.5-10%		
EINECS: 200-662-2  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336			

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

www.uhu.com 2/10

GB-FN



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB-EN

www.uhu.com 3/10



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

2 1 C	ontrol	parameters	(Contd. of p	
		with limit values that require monitoring	ng at the workplace:	
		thyl acetate		
		term value: 770 mg/m³, 250 ppm		
	Long-	term value: 616 mg/m³, 200 ppm		
64-17	7-5 eth	anol		
WEL	Long-	term value: 1920 mg/m³, 1000 ppm		
-	I-1 ace			
WEL		erm value: 3620 mg/m³, 1500 ppm		
	Ū	term value: 1210 mg/m³, 500 ppm		
DNE	_s			
79-20	)-9 me	thyl acetate		
Oral	Consumer, oral, longterm exposition		44 mg/kg bw/day	
Derm		Consumer, dermal, longterm exposition	44 mg/kg bw/day	
		Consumer, inhalation, longterm exposition	131 mg/m³	
64-17	7-5 eth	anol		
Oral	C	Consumer, oral, longterm exposition	87 mg/kg bw/day	
Derm		Consumer, dermal, longterm exposition	343 mg/kg bw/day	
Inhala	ative C	Consumer, inhalation, longterm exposition	950 mg/m³	
67-64	I-1 ace	tone		
Oral		Consumer, oral, longterm exposition	62 mg/kg bw/day	
Derm	al C	Consumer, dermal, longterm exposition	62 mg/kg bw/day	
Inhalative		Consumer, inhalation, longterm exposition	200 mg/m³	
PNEC	Cs			
79-20	)-9 me	thyl acetate		
Fresh	n water	0.12 mg/l		
Marin	e wate	r 0.012 mg/l		
Soil		0.0416 mg/kg		
64-17	7-5 eth	anol		
Fresh water		0.96 mg/l		
Marine water		r 0.79 mg/l		
Soil		0.63 mg/kg		
67-64	I-1 ace	tone		
Fresh	n water	10.6 mg/l		
Marine water		r 1.06 mg/l		
Soil		29.5 mg/kg		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Wash hands before breaks and at the end of work.

(Contd. on page 5)

- GB-EN -

www.uhu.com 4/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

(Contd. of page 4)

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

glove material: butyl rubber

thickness of the glove material: 0,6 - 0,8 mm

breakthrough time (maximum wearing time): 60 - 120 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye protection:



Tightly sealed goggles

Goggles recommended during refilling

### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:

Form:
Colour:
Colour:
Characteristic
Codour threshold:
Not determined.

PH-value:
Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** 55.8-56.6 °C

· Flash point: -13 °C

Flammability (solid, gas): Not applicable.

· Ignition temperature: 425 °C

· **Decomposition temperature:** Not determined.

(Contd. on page 6)

- GB-EN

www.uhu.com 5/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

	(Contd. of page
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapour pressure at 20 °C:	220 hPa
Density at 20 °C:	0.987 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	4400 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	65.9 %
Water:	0.4 %
VOC (EC)	65.85 %
Solids content:	33.8 %
9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable not relevant for the characterization of the mixture.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB-EN

www.uhu.com 6/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

			(Contd. of page 6)				
ſ	· LD/LC50 values relevant for classification:						
Γ	79-20-9 m	79-20-9 methyl acetate					
ľ	Oral	LD50	3705 mg/kg (rabbit)				
ľ	64-17-5 ethanol						
Ī	Oral	LD50	7060 mg/kg (rat)				
l	Inhalative	LC50/4 h	20000 mg/l (rat)				
ľ	67-64-1 acetone						
ľ	Oral	LD50	5800 mg/kg (rat)				
l	Dermal	LD50	20000 mg/kg (rabbit)				

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

2D EN

(Contd. on page 8)

www.uhu.com 7/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

(Contd. of page 7)

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number

· ADR/ADN, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES · IMDG, IATA ADHESIVES

· 14.3 Transport hazard class(es)

ADR/ADN



· Class 3 (F1) Flammable liquids.

Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler):

**EMS Number:** F-E,S-D

(Contd. on page 9)

GB-EN

www.uhu.com 8/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

	(Contd. of page
Stowage Category	A
· 14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.
· Transport/Additional information: · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml
Transport category Tunnel restriction code	3 E
·IMDG	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

(Contd. on page 10)

GB-EN

www.uhu.com 9/10



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Version number 2 Revision: 25.09.2019

Trade name: UHU All purpose 20ml Bl. EN

(Contd. of page 9)

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

10/10 www.uhu.com