Safety Data Sheet (SDS) Report

Suzhou xiongying ink technology co.LTD. Yun li road NO539 wujiang economic development zone of Suzhou city,China.

Sample Description:

Applicant:

The sample information was submitted and identified on client's behalf to be:

Product Name	:	Oil ball-pen ink
Physical State	:	Liquid
Data Received	:	Jul 03, 2018
Initial Version Date	:	Dec 15, 2015
Data Reviewed	:	Jul 05, 2018

Service Requested:

Based on the information provided by the applicant, the Safety Data Sheet (SDS) was generated according to requirements of Regulation (EC) No 1907/2006 (REACH) with its amendment Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008, for details please refer to attached pages.

Authorized By: On Behalf Of Regulatory Affairs in Intertek Testing Services Ltd., Shanghai

Annan

Anna Wang Regulatory Consultant

This report shall not be reproduced except in full, without the written approval of the laboratory.

Intertek Health, Environmental & Regulatory Services (HERS)

5th Floor,Building No.86,1198 QinZhou Road(North),Cao Hejing Development Zone,ShangHai,China. Tel: +86 021 53397917 ZIP: 200233 E-mail:hers@intertek.com

SDS number: WUXH0003777701

Issue Date:

2018-07-05

intertek Total Quality. Assured.

Project number: WUXH0003777701

Suzhou xiongying ink technology co.LTD. Version No:1.1 Safety Data Sheet (Conforms to Regulations (EC) No 2015/830)

Issue Date:05/07/2018 S.REACH.DEU.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1.Product Identifier

Product name	Oil ball- pen ink
Synonyms	Not Available
Other means of identification	Not Available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	For writting
Uses advised against	Not Applicable

1.3. Details of the supplier of the safety data sheet

Registered company name	Suzhou xiongying ink technology co.LTD.		
Address	Yun li road NO539 wujiang economic development zone of suzhou city, China.		
Telephone	+86-512-633313858		
Fax	+86-512-63320778		
Emergency telephone	+86-15962550010		
Email	zhangshenghong001@126.com		
Importer name			
Address			
Telephone			
Email			

1.4. Emergency telephone number

Association / Organisation	
Emergency telephone numbers	
Other emergency telephone numbers	+ 49 231 9071 2971(BAuA Information Centre)

SECTION 2 HAZARDS IDENTIFICATION

2.1.Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Chronic Aquatic Hazard Category 3
2.2. Label elements	
CLP label elements	
SIGNAL WORD	WARNING
Hazard statement(s)	
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation

H412

Harmful to aquatic life with long lasting effects

Not Applicable

Precautionary statement(s) Prevention

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

Cumulative effects may result following exposure*.

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.509-34-2 2.208-096-8 3.Not Available 4.Not Available	30	c.i. solvent red 49	Acute Toxicity (Oral) Category 4, Eye Irritation Category 2, Aquatic Chronic Category 3; H302, H319 ,H412
1.122-99-6 2.204-589-7 3.603-098-00-9 4.Not Available	25	ethylene glycol phenyl ether	Acute Toxicity (Oral) Category 4, Eye Irritation Category 2; H302, H319
1.100-51-6 2.202-859-9 3.603-057-00-5 4.Not Available	20	benzvl alcohol	Acute Toxicity (Inhalation) Category 4, Acute Toxicity (Oral) Category 4; H332, H302
1.25054-06-2 2.Not Available 3.Not Available 4.Not Available	14	keton resin	Not Applicable
1.24969-06-0 2.Not Available 3.Not Available 4.Not Available	6	Epoxy resin	Not Applicable
1.102-71-6 2.203-049-8 3.Not Available 4.Not Available	4	triethanolamine	Not Applicable
1.90506-69-7 2.291-933-4 3.Not Available 4.Not Available	1	phosphoric acid ester	Skin Corrosion/Irritation Category 1; H314

	► IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
	 For advice, contact a Poisons Information Centre or a doctor.
	 Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patients:
	condition.
	 If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.
	If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.
	Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
	 INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if
	possible) to maintain open airway and prevent aspiration.
General	NOTE: Wear a protective glove when inducing vomiting by mechanical means.
	<i>ии</i>
	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unpressented.
	Other measures are usually unnecessary. If this product comes in contact with the eyes:
	Wash out immediately with fresh running water.
	 Final real management of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
	 Seek medical attention without delay; if pain persists or recurs seek medical attention.
	Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
	If skin contact occurs:
	Immediately remove all contaminated clothing, including footwear.
	Flush skin and hair with running water (and soap if available).
	Seek medical attention in event of irritation.
	If this product comes in contact with the eyes:
	Wash out immediately with fresh running water.
Eye Contact	Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
	 Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
	If skin contact occurs:
Skin Contact	 Immediately remove all contaminated clothing, including footwear. Elvis add primitish priorities unter (and each if available).
	 Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area.
	Other measures are usually unnecessary.
	► IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
	For advice, contact a Poisons Information Centre or a doctor.
	Urgent hospital treatment is likely to be needed.
	In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
	If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be
	provided. Further action will be the responsibility of the medical specialist.
	If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.
Ingestion	
	Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed
	otherwise:
	INDUCE vomiting with fingers down the back of the threat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if
	possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
 Manifer and treat where a second for and structure.
- Monitor and treat, where necessary, for arrhythmias.
 Start or IV DEW TICE If the second second
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.

Treat seizures with diazepam.

Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Treat symptomatically.

Clinical experience of benzyl alcohol poisoning is generally confined to premature neonates in receipt of preserved intravenous salines.

Metabolic acidosis, bradycardia, skin breakdown, hypotonia, hepatorenal failure, hypotension and cardiovascular collapse are characteristic.

- High urine benzoate and hippuric acid as well as elevated serum benzoic acid levels are found.
- ▶ The so-called 'gasping syndrome describes the progressive neurological deterioration of poisoned neonates.
- Management is essentially supportive.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

5.3. Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include; carbon dioxide (CO2) aldehydes nitrogen oxides (NOx) other pyrolysis products typical of burning organic materialMay emit poisonous fumes.May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	 The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential. Any static discharge is also a source of hazard. Before any distillation process remove trace peroxides by shaking with excess 5% aqueous ferrous sulfate solution or by percolation through a column of activated alumina. The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example. Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised. A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation.
Safe handling	Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised. A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are

Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Polythene drum. Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
	 Benzyl alcohol: may froth in contact with water slowly oxidises in air, oxygen forming benzaldehyde is incompatible with mineral acids, caustics, aliphatic amines, isocyanates reacts violently with strong oxidisers, and explosively with sulfuric acid at elevated temperatures corrodes aluminium at high temperatures is incompatible with aluminum, iron, steel attacks some nonfluorinated plastics; may attack, extract and dissolve polypropylene Benzyl alcohol contaminated with 1.4% hydrogen bromide and 1.2% of dissolved iron(II) polymerises exothermically above 100 deg. C.
Storage incompatibility	 Glycol ethers may form peroxides under certain conditions; the potential for peroxide formation is enhanced when these substances are used in processes such as distillation where they are concentrated or even evaporated to near-dryness or dryness; storage under a nitrogen atmosphere is recommended to minimise the possible formation of highly reactive peroxides Nitrogen blanketing is recommended if transported in containers at temperatures within 15 deg C of the flash-point and at or above the flash-point - large containers may first need to be purged and inerted with nitrogen prior to loading In the presence of strong bases or the salts of strong bases, at elevated temperatures, the potential exists for runaway reactions. Contact with aluminium should be avoided; release of hydrogen gas may result-glycol ethers will corrode scratched aluminium surfaces. May discolour in mild steel/ copper; lined containers, glass or stainless steel is preferred Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water . Avoid strong bases. Avoid strong bases. Avoid strong bases.

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL) Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Germany Recommended Exposure Limits - MAK Values (English)	ethylene glycol phenyl ether	2-Phenoxyethanol	110 mg/m3 / 20 ppm	I (2) ppm	Not Available	Not Available
Germany TRGS 900 - Limit Values for the Workplace Atmosphere (German)	ethylene glycol phenyl ether	2-Phenoxyethanol	110 mg/m3 / 20 ppm	Not Available	Not Available	Not Available
Germany Recommended Exposure Limits - Substances for which no MAK value can be established at present	benzyl alcohol	Benzyl alcohol	Not Available	Not Available	Not Available	Not Available
Germany Recommended Exposure Limits - MAK Values (English)	triethanolamine	Triethanolamine	5 mg/m3	l(4) ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethylene glycol phenyl ether	Phenoxyethanol, 2-; (Phenyl cellosolve)	20 ppm	20 ppm	44 ppm
benzyl alcohol	Benzyl alcohol	30 ppm	49 ppm	49 ppm
triethanolamine	Triethanolamine; (Trihydroxytriethylamine)	15 mg/m3 51 mg/m3 1100 mg/m3		
In one diamet		Davies d IDI II		
Ingredient	Original IDLH	Revised IDLH		
All ingredients	Not Available	Not Available		

	8.2.	Exposure	controls
--	------	----------	----------

8.2.1. Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment.
8.2.2. Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream.
Thermal hazards	Not Available

Respiratory protection

Type ABK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Red Liquid		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Flammable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

Page 7 of 12

Oil ball- pen ink

10.2.Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3
SECTION 11 TOXICOLOG	GICAL INFORMATION

11.1. Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of benzyl alcohol may affect breathing (causing depression and paralysis of breathing and lower blood pressure.				
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of large doses of benzyl alcohol may cause abdominal pain, nausea, vomiting, diarrhea. It may affect behavior/central nervous system and cause headache, somnolence, excitement, dizziness, ataxia, coma, convulsions, and other symptoms of central nervous system depression. Exposure to excessive amounts of benzyl alcohol has been associated with toxicity (hypotension, metabolic acidosis), particularly in neonates, and an increase incidence of kernicterus (a neurological condition that occurs in severe jaundice), particularly in small preterm infants. There have been rare reports of death primarily in preterm infants, associated with exposure to excessive amounts of benzyl alcohol.				
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Toxic effects may result from skin absorption Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			/ with harmful effects. Examine the skin prior to the use	
Eye	This material can cause eye irritation and damage in some persons.				
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Reactions to benzoic acid have been reported. It may worsen asthma, skin rash or skin disease (angio-oedema). Effect may be worse if exposed persons are also taking aspirin tablets. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Prolonged or repeated exposure to benzyl alcohol may cause allergic contact dermatitis. Prolonged or repeated ingestion may affect behavior/central nervous system with symptoms similar to acute ingestion. It may also affect the liver, kidneys, cardiovascular system, and metabolism (weight loss). Animal studies have shown this compound to cause lung, liver, kidney and CNS disorders. Ethylene glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.				
Oil ball- pen ink	TOXICITY IRRITATION				
	Not Available Not Ava		silable		
c.i. solvent red 49	TOXICITY Oral (rat) LD50: 1830 mg/kg ^[2]			IRRITATION [Manufacturer]	
	TOXICITY IRRITATION				
othylong glygol phonyl othor	dermal (rat) LD50: 14391 mg/kg ^[1] Eye (rabbit): 250		bbit): 250 ug/24h	- SEVERE	
ethylene glycol phenyl ether	Oral (rat) LD50: 1386 mg/kg ^[1] Eye (rabbit): 6		bbit): 6 mg - mod): 6 mg - moderate	
		Skin (rabbit): 500 mg/24h - mild		h - mild	
	TOXICITY	IRRITATION			
benzyl alcohol				an): 16 mg/48h-mild	
	Inhalation (rat) LC50: >4.178 mg/L/4h ^[2] Skin (rabbit):10 mg/24h open-mild		24h open-mild		
	Oral (rat) LD50: 1560 mg/kg ^[2]				
	ΤΟΧΙCΙΤΥ		IRRITATION		
	dermal (rat) LD50: >18080 mg/kg ^[2]			IRRITATION Eve (rabbit): 0.1 ml -	
	Oral (rat) LD50: 5559.6 mg/kg(female) * ^[2]		Eye (rabbit): 0. I mi - Eye (rabbit): 10 mg - mild		
triethanolamine			minor conjunctival irritation		
			minor iritis,		
			no corneal inju	ry *	
	L		no irritation *		

	Skin (human): 15 mg/3d (int)-mild			
	Skin (rabbit): 4 h occluded			
	Skin (rabbit): 560 mg/24 hr- mild			
	with significant discharge;			
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			

Acute Toxicity	✓	Carcinogenicity	0
Skin Irritation/Corrosion	×	Reproductivity	\otimes
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	\otimes
Mutagenicity	\otimes	Aspiration Hazard	0
		Legend: ¥	- Data available but does not fill the criteria for classification

Data required to make classification available

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
c.i. solvent red 49	EC50	96	Algae or other aquatic plants	0.021mg/L	3
c.i. solvent red 49	LC50	96	Fish	0.223mg/L	3
ethylene glycol phenyl ether	EC50	384	Crustacea	25.027mg/L	3
ethylene glycol phenyl ether	EC50	96	Algae or other aquatic plants	429.444mg/L	3
ethylene glycol phenyl ether	LC50	96	Fish	106.514mg/L	3
ethylene glycol phenyl ether	NOEC	24	Fish	5mg/L	2
ethylene glycol phenyl ether	EC50	48	Crustacea	460mg/L	2
benzyl alcohol	EC03	168	Algae or other aquatic plants	=16mg/L	4
benzyl alcohol	LC50	96	Fish	10mg/L	4
benzyl alcohol	NOEC	336	Fish	5.1mg/L	2
benzyl alcohol	EC50	48	Crustacea	230mg/L	2
benzyl alcohol	EC50	72	Algae or other aquatic plants	500mg/L	2
Epoxy resin	EC50	96	Algae or other aquatic plants	132.133mg/L	3
Epoxy resin	LC50	96	Fish	0.450mg/L	3
triethanolamine	LC50	96	Fish	0.0011807mg/L	4
triethanolamine	EC10	96	Algae or other aquatic plants	7.1mg/L	1
triethanolamine	EC50	48	Crustacea	609.88mg/L	2
triethanolamine	NOEC	504	Crustacea	16mg/L	2
triethanolamine	EC50	72	Algae or other aquatic plants	>107- <260mg/L	2

Legend:

Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come incontact with surface waters or to intertidal areas below the mean high watermark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of theproduct must be disposed of on site or at approved waste sites.

For Ethelene Glycol MonoalkylEthers and their Acetates:

log BCF: 0.463 to 0.732;

LC50 : 94 to > 5000 mg/L.(aquatic species).

Members of this category includeethylene glycol propyl ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE).

Environmental Fate: Aquatic Fate - The ethers possess no functional groups that are readily subject to hydrolysisin the presence of waters.

For solvent dyes:

Environmental Fate: Solvent dyesare characterised as non-ionic or neutral dyes, and are hydrophobic incharacter and thus solubility in water is low, ranging from 0.2 mg/l to 34.3 mg/l. Solvent dyes, like the disperse dyes, are hydrophobic. However, due totheir large, complex molecular structure, they have lower vapour pressures thandisperse dyes. The partition coefficients (Kow) are very high for the non-ionicdyes (in the range of 420 for Solvent Yellow 1 to 11,220 for Solvent Yellow 2).

For Glycol Ethers:

Environmental Fate: Several glycolethers have been shown to biodegrade however; biodegradation slows as molecularweight increases. No glycol ethers that have been tested demonstrate markedresistance to biodegradative processes. No glycol ethers that have been testeddemonstrate marked resistance to biodegradative processes

Atmospheric Fate: Upon release to the atmosphere by evaporation, high boiling glycol ethers are estimated toundergo photo-degradation (atmospheric half lives = 2.4-2.5 hr). For Benzyl Alkyl Alcohols: Log Kow: 1.36 to 2.06; Vapor Pressure: 0.01 to 0.1 hPa (@ room temperature); Water Solubility: >5x10+3 mg/L.

Environmental Fate: Benzyl alkyl alcohols are liquids, under standard temperature and pressure conditions. These substances will partition primarily to the soil, secondarily to the water, and very

slightly to the air.

Atmospheric Fate: Benzyl alcohol is expected to exist almost entirely in the vapor phase, in the ambient atmosphere.

For benzoates:

The environmental characteristics for benzoates is ultimately determined by the properties of counter-ions, and is assumed to be non-toxic.

Environmental Exposure and Fate: Distribution models indicate that water and soil are the main environmental pathways of benzyl alcohol, benzoic acid, sodium and potassium benzoates.

Novolalization to the atmosphere or adsorption to sediments is expected. Physicalchemical properties and use patterns indicate water to be the main pathway forthese substances, however, based

on the chemical structure and organicchemistry, no hydrolysis is expected at pH ranges of 4 - 11.

For benzyl alcohol: log Kow :1.1Koc : <5Henry's atm m3 /mol: 3.91E-07BOD 5: 1.55-1.6,33-62%COD : 96%ThOD: 2.519BCF : 4

Bioaccumulation: Not significant

Anaerobic Effects: Significantdegradation. Effects on algae and plankton:Inhibits degradation of glucose Degradation Biological:Significant processes

Abiotic: RxnOH*,no photochem

Ecotoxicity: Fish LC50 (48 h):fathead minnow 770 mg/l; (72 h): 480 mg/l; (96 h) 460 mg/l. Fish LC50 (96 h)fathead minnow 10 ppm, bluegill sunfish 15 ppm; tidewater silverside fish 15ppm. Products of Biodegradation: Possibly hazardous short term degradationproducts are not likely. DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
c.i. solvent red 49	HIGH	HIGH
ethylene glycol phenyl ether	LOW	LOW
benzyl alcohol	LOW	LOW
Epoxy resin	LOW	LOW
triethanolamine	LOW	LOW

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
c.i. solvent red 49	HIGH (LogKOW = 6.6307)
ethylene glycol phenyl ether	LOW (LogKOW = 1.16)
benzyl alcohol	LOW (LogKOW = 1.1)
Epoxy resin	LOW (LogKOW = 0.912)
triethanolamine	LOW (BCF = 4)

12.4. Mobility in soil

Ingredient	Mobility
c.i. solvent red 49	LOW (KOC = 3828000)
ethylene glycol phenyl ether	LOW (KOC = 12.12)
benzyl alcohol	LOW (KOC = 15.66)
Epoxy resin	MEDIUM (KOC = 2.443)
triethanolamine	LOW (KOC = 10)

12.5.Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

	Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
Product / Packaging	▶ Reuse
disposal	▶ Recycling
	▶ Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Authority for disposal.
	Bury or incinerate residue at an approved site.
	 Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available

Page 10 of 12

Oil ball- pen ink

Sewage disposal options Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1.UN number	Not Applicable			
14.2.Packing group	Not Applicable			
14.3.UN proper shipping name	Not Applicable			
14.4.Environmental hazard	Not Applicable			
14.5. Transport hazard class(es)	ClassNot ApplicableSubriskNot Applicable			
14.6. Special precautions for user	Hazard identification (Kemler)Not ApplicableClassification codeNot ApplicableHazard LabelNot ApplicableSpecial provisionsNot ApplicableLimited quantityNot Applicable			

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. Packing group	Not Applicable		
14.3. UN proper shipping name	Not Applicable		
14.4. Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	ICAO/IATA ClassNot ApplicableICAO / IATA SubriskNot ApplicableERG CodeNot Applicable		
14.6. Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable	

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. Packing group	Not Applicable		
14.3. UN proper shipping name	Not Applicable		
14.4. Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	IMDG ClassNot ApplicableIMDG SubriskNot Applicable		
14.6. Special precautions for user	EMS NumberNot ApplicableSpecial provisionsNot ApplicableLimited QuantitiesNot Applicable		

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number Not Applicable

Page 11 of 12

Oil ball- pen ink

		R .	
14.2. Packing group	Not Applicable		
14.3. UN proper shipping name	Not Applicable		
14.4. Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	Not Applicable Not Applicable		
14.6. Special precautions for user	Classification codeNot ApplicableSpecial provisionsNot ApplicableLimited quantityNot ApplicableEquipment requiredNot ApplicableFire cones numberNot Applicable		
ransport in bulk accordi	ng to Annex II of MARPOL 73 / 78 and the IBC co	ode	
Source	Ingredient		Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethylene glycol phenyl ether		Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	benzyi alcohol		Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	triethanolamine		z
C.I. SOLVENT RED 49(509-34-	vironmental regulations / legislation specific fo 2) IS FOUND ON THE FOLLOWING REGULATORY LISTS		
European Customs Inventory of (Chemical Substances ECICS (English)	European Union - Euro (English)	pean Inventory of Existing Commercial Chemical Substances (EINE
ETHYLENE GLYCOL PHENYL	ETHER(122-99-6) IS FOUND ON THE FOLLOWING REGUL	LATORY LISTS	
European Union - European Inve	Chemical Substances ECICS (English) ntory of Existing Commercial Chemical Substances (EINECS)	Classifications & Germ	•
(English) European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of		Germany Recommended Exposure Limits - MAK Values (English) Germany TRGS 900 - Limit Values for the Workplace Atmosphere (German)	
European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI		International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	
BENZYL ALCOHOL(100-51-6)	IS FOUND ON THE FOLLOWING REGULATORY LISTS		
EU European Chemicals Agency Substances	(ECHA) Community Rolling Action Plan (CoRAP) List of	European Union (EU) A Dangerous Substances	Annex I to Directive 67/548/EEC on Classification and Labelling of 6 - updated by ATP: 31
European Customs Inventory of Chemical Substances ECICS (English) European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)		European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI	
(English)		Germany Recommende established at present	ed Exposure Limits - Substances for which no MAK value can be
KETON RESIN(25054-06-2) IS Not Applicable	FOUND ON THE FOLLOWING REGULATORY LISTS		
EPOXY RESIN(24969-06-0) IS	FOUND ON THE FOLLOWING REGULATORY LISTS		
, ,	Chemical Substances ECICS (English)		

TRIETHANOLAMINE(102-71-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of

Substances

European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

PHOSPHORIC ACID ESTER(90506-69-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: 67/548/EEC, 1999/45/EC, 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments as well as the following British legislation: - The Control of Substances Hazardous to Health Regulations (COSHH) 2002 - COSHH Essentials - The Management of Health and Safety at Work Regulations 1999

Germany Recommended Exposure Limits - MAK Values - Pregnancy Risk Group

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Germany Recommended Exposure Limits - MAK Values (English)

Classifications & Germ Cell Mutagens

Monographs

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

Continued...

15.3. Classification of Substances and Mixtures into Water Hazard Classes

PREPARATION IS WGK 1

News	WOK	Contra	Courses	
Name	WGK	Score	Source	
c.i. solvent red 49	1	1	W: VwVwS	
ETHYLENE GLYCOL PHENYL ETHER	1		W: VwVwS	
BENZYL ALCOHOL	1		W: VwVwS	
keton resin	1	0	W: VwVwS	
Epoxy resin	1	0	W: VwVwS	
TRIETHANOLAMINE	1		W: VwVwS	
phosphoric acid ester	1	0	W: VwVwS	
National Inventory	Status			
Australia - AICS	N (phosphoric acid ester)			
Canada - DSL	N (phosphoric acid ester)	N (phosphoric acid ester)		
Canada - NDSL	N (benzyl alcohol; Epoxy resin; keton resin; c.i. solvent red 49; triethanolamine; phosphoric acid ester; ethylene glycol phenyl ether)			
China - IECSC	Υ			
Europe - EINEC / ELINCS / NLP	N (Epoxy resin; keton resin)			
Japan - ENCS	N (phosphoric acid ester)	N (phosphoric acid ester)		

N (phosphoric acid ester)	
N (phosphoric acid ester)	
N (Epoxy resin; phosphoric acid ester)	
N (phosphoric acid ester)	
N (phosphoric acid ester)	
Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Full text Risk and Hazard codes

H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled

Other information

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

- PC-STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit_ $\ensuremath{\mathsf{IDLH}}$ Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index