



# CARPET PROTECTION FILM

Read this manual in full before using this product and retain it for future use. Always use the latest version of the manual. For the latest version of this manual please visit [drapertools.com/manuals](https://www.drapertools.com/manuals)

## 1. Scope and Specification

This product is designed for temporary protection of carpeted flooring from paint, dirt, debris and damage from heavy footfall and can be used on flat carpet or stairs. Any other application beyond the conditions established for use will be considered misuse. Draper Tools accepts no responsibility for improper use of this product.

**Important:** This product is intended for temporary use and is not suitable for permanent application over extended periods. **DO NOT** use this product on hard surfaces.

Stock No.	18018
Part No.	CPF/2
Width	600mm
Length	25m
Application	Carpet
Best before	12 months from the date of purchase

# EN

Original Instructions  
Version 1 – October 2022

## 2. Notes on Use

**Important:** Read these instructions in full before using this product. Failure to adhere to these instructions may result in damage to the covered surface.

**Important:** Responsibility for determining the suitability of this product for the surface lies with the customer. If you are in any way unsure, contact Draper Tools for support.

- This product is suitable for use on carpets **ONLY**.
  - **DO NOT** use this product on hard surfaces.
  - Draper Tools recommends that this product is **NOT** used on wool, antique or oriental carpets, rugs or loosely fitted carpet tiles.
- **ALWAYS** ensure that the surface to be covered is clean, dust-free, dry and sound before use.
  - Draper Tools recommends vacuuming the area to be covered before use.
  - Use on surfaces that are not “sound” may result in damage to the surface or any finishes or coatings applied.
- **DO NOT** use this product in outdoor or high-humidity environments.
- **DO NOT** use this product on newly-laid carpets where adhesives have been used.
  - Allow at least 72 hours for the vapours to evaporate before application.
- **DO NOT** use this product on carpets that have been recently cleaned.
  - Allow at least 10 days for the carpet to thoroughly dry before use.
- **DO NOT** switch on any under-floor heating beneath the covered surface while the product is in place.
- Draper Tools strongly recommends testing the product on a small, discreet area for 48 hours before full use to assess the risk of damage to the surface.
- This product may become slippery when wet.
  - Clear up any spillages or puddling immediately and allow the film to dry or replace the film before continuing work.
- In some circumstances, the product may leave a sticky residue on the covered surface.
  - Use warm, soapy water or carpet cleaning products to remove any transferred adhesive.
- To reduce the risk of damage or residue, remove the product from the surface

after no more than four weeks under normal conditions.

- In areas that experience significantly increased footfall or ambient temperatures of greater than 22°C, remove the product from the surface after no more than one week.

**Important: ALWAYS** ensure that the product is firmly secured before working near the surface.

### 3. Application Instructions

**Important:** Read these instructions in full before use. Test the product on a small and discreet area for 48 hours before full application.

**Important:** For best results, use this product within 12 months of purchase; performance may be reduced after this time.

1. Remove the outer packaging.
2. Place the product onto the surface in the direction that it will be applied and unwind the film approximately 300mm.
3. Smooth out the unwound area and ensure that it is stuck securely to the surface with minimal air bubbles.
4. Slowly push the roll forward, ensuring it travels in a straight line, and smooth the film against the surface using your hands, feet or a soft brush to remove any air bubbles.
5. Cut the film to size using a sharp knife or scissors, taking care not to damage the surrounding surfaces.
6. Remove the film from the surface within four weeks of application, or within one week in areas of significantly heavy footfall or where temperatures exceed 22°C.
7. Clean any sticky residue from the surface using warm, soapy water or suitable carpet cleaning products.

**Important:** Single use only. **DO NOT** reuse film once it has been removed from the surface.

### 4. Storage and Disposal

- Store this product in a clean and dry environment, out of reach of children.
- Store this product in ambient temperatures of 5–25°C.
- Dispose of this product responsibly and in accordance with local regulations.

**0.6M**  
**x**  
**25M**

Product dimensions

© Published by Draper Tools Limited

Helpline: +44 (0) 23 8049 4344 Sales Desk: +44 (0) 23 8049 4333 General Enquiries: +44 (0) 23 8026 6355 Website: [drapertools.com](http://drapertools.com) Email: [sales@drapertools.com](mailto:sales@drapertools.com)

Draper Tools Limited, Hursley Road, Chandler's Ford, Eastleigh, Hampshire, SO53 1YF, UK

Delta International, Delta International BV, Oude Graaf 8, 6002 NL, Weert, Netherlands