

## 230V Industrial Dehumidifier, 1300W, 70L

**STOCK No.** 12500 **BRAND** Draper

**BARCODE** 5059482061608

**WARRANTY** 12 months parts and labour

---

### FEATURES

- Capable of extracting up to 70L of moisture from the air per day
  - Digital control panel features auto-defrost, auto-reset and 24-hour timer
  - Fitted with 100cm x 16mm long hose for continuous drainage
  - Washable air filter
  - Wheels and handle for easy manoeuvrability
  - Refrigerant R290 (propane based)
- 



### DESCRIPTION

This large portable dehumidifier is capable of extracting up to 70L of moisture from the air per day. It is suitable for large spaces up to 160m<sup>2</sup> (minimum size - 14m<sup>2</sup>) to prevent the build-up of mildew and mould. It is equipped with a digital control panel and features auto-defrost, auto-reset and 24-hour timer. The air filter is removable and washable for convenient cleaning. Fitted with 100cm x 16mm long hose for continuous drainage. The steel frame ensures high durability and long service life. Fitted with large wheels and a handle for easy manoeuvrability. Uses refrigerant R290 (propane based).

---

### CONTENTS

1 x 230V Industrial Dehumidifier, 1300W, 70L

[Link to product - drapertools.com](https://www.drapertools.com)

**SPECIFICATIONS**

|                               |                                              |
|-------------------------------|----------------------------------------------|
| Voltage                       | 230V                                         |
| Power                         | 1,300W                                       |
| Extraction rate               | 70L per day (at 30°C, 80% relative humidity) |
| Target humidity range         | 10-95%                                       |
| Discharge hose length         | 100cm                                        |
| Discharge hose outlet         | Ø16mm                                        |
| Refrigerant                   | R290 (propane), 280g                         |
| Maximum suction pressure      | 1.0Mpa                                       |
| Maximum discharge pressure    | 2.5Mps                                       |
| Minimum room size             | 14m2                                         |
| Ambient operation environment | 5-35°C                                       |
| Global warming potential      | 3                                            |
| Ingress protection            | IP22                                         |
| Dimensions                    | W 545 x H 870 x D 460mm                      |
| Weight                        | 40kg                                         |

**DOCUMENTS**



Instruction Manual



Declaration Of  
Conformity UK CA



Declaration Of  
Conformity CE



Material Safety Data  
Sheet