



**ELECTRONIC CHARGERS**

SPX 459 ⚡ 12 V 🔌 6 A



Worry-free charging.  
Maintain all season.



+++

Battery charger and maintainer

For 12V batteries up to 130 Ah

Microprocessor controlled

Protection against: Reverse polarity, spark proof and thermal runaway

AGM, Standard, gel, calcium, Start n' Stop, Lithium (LiFePo4)

Hook attachment

Protective bumpers

Fully automatic and safety shut-off



# SPX RANGE



## TECHNICAL INFORMATION

MODEL	SPX 457	SPX 458	SPX 459	SPX 460
PART NUMBER	94065457*	94065458*	94065459*	94065460*
	* Add letter plug type PLUG EU = C PLUG UK = G PLUG AU = I			
VOLTAGE (DC)	6/12 V	12 V	12 V	12 V
NOMINAL AC VOLTAGE	230V AC - 50 HZ			
MAX. CHARGING CURRENT	1A	3A	6A	10A
IP RATING	IP64	IP64	IP64	IP64
BATTERY TYPE	Lead-Acid & Lithium	Lead-Acid & Lithium	Lead-Acid & Lithium	Lead-Acid & Lithium
OUTPUT CABLE (CM) (FROM ENCLOSURE TO CLAMP END)	191	191	195	195
WORKING TEMPERATURE	-20° to +50° C			



## PACKAGING INFORMATION

MODEL	SBX 457	SBX 458	SBX 459	SBX 460
NET WEIGHT (KG)	0,78 kg	0,86kg	1,37 kg	1,37 kg
DIMENSIONS ( L x W x h ) mm	131 x 101 x 204	105 x 137 x 210	163 x 136 x 218	163 x 136 x 218

## HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	6 V	12 V							
			12 Ah	32 Ah	46 Ah	58 Ah	130 Ah	165 Ah	200 Ah	230 Ah	
94065457	SPX 457	6/12 V	■	■							
94065458	SPX 458	12 V		■	■	■					
94065459	SPX 459	12 V		■	■	■	■				
94065460	SPX 460	12 V		■	■	■	■	■			