

Philips Signage Solutions
OPS accessory

HDbaseT receiver
OPSinsert compatible

SignageSolutions

CRD25

# Future Proof Connectivity

With HDBaseT OPS receiver

Making use of leading technology standards, the HDBaseT OPS receiver integrated within the OPSinsert provides you with a powerful combination and a unique all-in-one solution

# Innovative solutions for any signage application

- Optional OPS Insert to create an all-in-one solution
- OPS receiver module enables reception of HDbaseT signals



# CRD25/00

# Specifications

#### **Related Products**

· Compatible with: BDL4256ET, BDL4260EL, BDL4271VL, BDL4280VL, BDL4660EL, BDL4671VL, BDL4677XH, BDL4678XL, BDL4680VL, BDL4765EL, BDL5551EL, BDL5556ET, BDL5560EL, BDL5571VL, BDL5580VL, BDL5588XH, BDL5588XL

### **Supported Display Resolution**

Computer formats	
Resolution	Refresh rate
1280 x 768	60Hz
1280 x 800	60Hz
$1360 \times 768$	60Hz
1366 x 768	60Hz
1440 × 900	60Hz
1920 x 1080p	60Hz
640 x 480	60, 67, 72, 75Hz

56, 60, 72, 75Hz  $800 \times 600$ Video formats

Resolution	Refresh rate
1080i	50, 60Hz
1080 <sub>P</sub>	50, 60Hz
480i	60Hz

480p 60Hz 576i 50Hz 576p 50Hz 50, 60Hz 720p

#### **Dimensions**

• Set dimensions (W x H x D): 141.1 x 23.5 x 105.8 mm

# Operating conditions • Altitude: 0 ~ 3000 m • Relative humidity: 20 ~ 80 %

- Temperature range (operation): 0  $\sim$  40  $^{\circ}$ C
- Temperature range (storage): -20 ~ 60 °C
- MTBF: 60,000 hour(s)

### **Miscellaneous**


- Regulatory approvals: CB, CE, C-Tick, FCC, Class B, RoHS, UL/cUL, VCCI
- · Warranty: 3 year warranty

### **Accessories**

• Included accessories: Quick start guide, RS232 cable

### OPSInsert





# Highlights

### **OPS** Insert



Turn your display into an all-in-one digital signage solution and create a display network which is connected, intelligent and secure. Open Pluggable Specification (OPS) is an industry standard slot into which you can add an OPS-standardized media player. This cable free solution gives you the ability to install, use or maintain your hardware whenever you need.

## **HDbaseT signals**



HDbaseT is a connectivity standard over a single CAT5e / 6 cable, converging uncompressed full HD digital video, audio signals.



Issue date 2014-11-26

© 2014 Koninklijke Philips N.V. All Rights reserved.

Version: 3.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 11649 EAN: 87 12581 71116 0

www.philips.com