SA746PU



Display size **32"- 50"**



Max load **80lb (36kg)**

SMARTMOUNT

Articulating Wall Mount

FOR 32" TO 50" DISPLAYS

The SmartMount® Articulating Wall Mount series offers the most versatile installation features and mounting options. The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display. Vertical adjustment ability allows for post installation leveling, making it easier than ever to find the perfect display position. With SA746PU, extend the display up to 22.22" (564mm) or fully-retract it to just 3.46" (88mm) from the wall for the perfect viewing position. The display can now simply be installed by a single person with the Hook-and-Hang™ system. One-Touch™ tilt technology offers +15°/-5° vertical tilt movement for the ideal viewing angle. Integrated cable management protects, contains and conceals cables for a clean installation.

Full-motion capabilities allow you to swivel, tilt, extend or retract your display for the perfect viewing angle.

Additional Features

- Retracts to hold display just 3.46" (88mm) from the wall
- ±90° of pivot allows for perfect display positioning
- ☑ Quick and easy, Hook-and-Hang[™] one-person installation
- The I-Shaped Adaptor plate's innovative design helps avoid blocking connections on back of display
- Universal mount fits displays with mounting patterns 200 x 100 to 400 x 400mm
- Landscape or portrait mounting options increases display versatility
- Includes all necessary wall and display attachment hardware
- Design is UL listed and tested to four times stated load capacity

■ POST INSTALLATION HEIGHT ADJUSTMENT ±0.5" (13mm) of vertical adjustment fine tunes positioning of display after installation ONE-TOUCH™ TILT +15°/-5° vertical tilt movement for the ideal viewing angle **EXTENDS UP TO 22.22" (564mm)** Offers the perfect viewing angle FLEXIBLE MOUNTING **LOCATIONS** Mounts to wood stud, concrete, cinder or breeze block INTEGRATED CABLE MANAGEMENT Protects, contains and conceals cables for a clean, professional installation ADAPTOR PLATE DESIGN



Swivel, tilt, extend or retract the display for the perfect viewing angle



Integrated cable management keeps cords and cables out of the way



Helps avoid blocking connections on back of display

Comes in color packaging with included installation hardware and easy to follow instructions.

RoHS os pd

Please visit peerless-av.com/en-us/patents for patent information.

SA746PU

SmartMount® Articulating Wall Mount for 32" to 50" Displays

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
SA746PU	18.19" x 16.75" x 3.46"-22.22" (462 x 425 x 88-564mm)	10.36lb (4.70kg)	80lb (36kg)	Scratch resistant fused epoxy	Semi-gloss black


Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SA746PU	20.38" x 5.13" x 12.50" (518 x 130 x 318mm)	11.9lb (5.4kg)	735029271901	Wall mount, wall and display installation hardware, installation instructions	1


Accessories


WSP700/WSP701: Metal Stud Wall Plates for 16"/24" Center Metal Studs

All dimensions = inch (mm)



TOP VIEW






WALL PLATE DETAIL



SIDE VIEW COLLAPSED



SIDE VIEW EXTENDED +15°/-5° TILT

Architect Specifications

The Smartmount® Articulating Wall Mount shall be a Peerless-AV model SA746PU and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV Europe

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV de México

Ave de las Industrias 413
Parque Industrial Escobedo
Escobedo, N.L.,
Mexico 66050

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

