
LX-1350

DATASHEET / BROCHURE





With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

This wide-carriage 9-pin printer fits perfectly into a range of environments including data reporting, listings and point-of-sale. It is 337 cps fast, very reliable and cost efficient and has a range of options so you can create the perfect high quality printer to match your changing business requirements.

Flexible working

Handle light duties in style with printing up to A3 size, 5-part forms (1 original + 4 copies) and 337 cps (12cpi) speed.

Get connected

Enjoy no-fuss support for a range of office equipment with auto switching between USB, parallel and serial sources.

Optional extras

Choose from a wide range of options to match changing needs, including a 50 cut-sheet feeder, and roll paper holder.

KEY FEATURES

- Wider format Fast, reliable 9-pin printing up to A3
- High productivity Print up to 337 characters per second (12 cpi)
- Multi-part flexibility Print up to 5-part forms (1 original 4 copies)
- Paper handling Top, bottom, front and rear paper paths
 Easy connectivity
- Auto switch between USB, parallel, serial sources



PRODUCT SPECIFICATIONS

| TECHNOLOGY | | |
|---------------------------------|--|--|
| Number of Pins | 9 pins | |
| Number of columns | 136 columns | |
| PRINT | | |
| Printing Speed | HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: | |
| | 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s | |
| Barcodes | Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5, | |
| | Matrix 2 of 5, POSTNET, UPC-A, UPC-E | |
| Carbon Copies | 4 plus one original | |
| Printing Resolution | 240 x 144 DPI | |
| CONNECTIVITY | | |
| Interfaces | USB 2.0-A, Bidirectional parallel, RS-232 | |
| PAPER / MEDIA HANDLING | | |
| Document Feed | Single sheet rear, Continuous media rear, Paper output rear | |
| Paper Formats | Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels | |
| | (single- and multi-layer), Roll Paper, Envelopes | |
| Paper Thickness Continuous | 0.065 mm - 0.39 mm | |
| Paper | | |
| Paper Thickness Multi Part | 0.14 mm - 0.39 mm | |
| Paper Thickness Single Sheet | t 0.065 mm - 0.14 mm | |
| GENERAL | | |
| Power consumption | 33 Watt, 1.1 Watt (standby) | |
| Supply Voltage | AC 220 V - 240 V | |
| Product dimensions | 546 x 275 x 164 mm (Width x Depth x Height) | |
| Product weight | 6.6 kg | |
| Supported Temperature | Operation 5° C - 35° C, Storage 5° C - 35° C | |
| Compatible Operating Systems | Windows 2000, Windows 7, Windows 8, Windows 98, Windows Server 2008 R2, Windows XF | |
| Included Software | Epson Status Monitor | |
| Mean Time Between Failures | • | |
| Print Head Life | 400 Million Strokes/Wire | |
| Noise | Operation: 53 dB (A) | |
| Memory | 128 kB Included | |
| Ribbon Yield | 4000000 characters Black Draft | |
| | | |
| | | |
| OTHER FEATURES | | |
| Emulations | ESC/P, IBM PPDS | |
| | ESC/P, IBM PPDS 128 kB | |
| Emulations | | |
| Emulations Input Data Buffer | | |

LOGISTICS INFORMATION

| sкu | C11CD24301A0 |
|-------------------|---------------|
| EAN code | 8715946540573 |
| Country of Origin | Indonesia |
| Layer | 3 Units |
| Layer Block | 3 Units |

LX-1350

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

• SIDM Black Ribbon Cartridge (C13S015642)

OPTIONAL ACCESSORIES

 Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2022-05-04

