



Model #: B055-001-UV2CAC

KVM Switch Accessories - USB Server Interface Unit with Virtual Media & CAC Support for B064-Series NetDirector Cat5 KVM Switches



Highlights

- Connect a USB server to a B064- IPG Series NetDirector KVM switch via Cat5e/6 cable
- Provides the connected server with access to Virtual Media
- Support for Common Access Card (CAC)
- Allows a maximum distance of 164 ft. (50 m.) from KVM to Server via Cat5e/6 cable
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Requires a B064- IPG KVM switch with firmware v1.0.071 or later installed

Description

Tripp Lite's USB Server Interface Unit with Virtual Media and Common Access Card (CAC) support connects a USB server to a B064- IPG Series NetDirector KVM switch using Cat5e/6 cabling. The server connected using this interface unit will be able to access the Virtual Media functionality of the B064- IPG series KVM switch. Use of Cat5e/6 cables frees up space in server cabinets that would otherwise be filled by traditional, bulkier KVM cable kits. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

- Server or CPU with a HD15 connector and USB type A connector
- A B064- IPG Series NetDirector Cat5 KVM Switch with firmware v1.0.071 or later installed
- Cat5e/6 cable

Package Includes

• Interface Unit with Virtual Media and Common Access Card (CAC) support

Features

- Provides the connected server with access to Virtual Media
- Supports Common Access card (CAC)
- Eliminates the need for thicker, heavier KVM cable kits
- Compact, lightweight design
- Plug and Play; no software required
- No power supply required
- 164 ft. (50 m.) distance from KVM switch
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Requires a B064- IPG KVM switch with firmware v1.0.071 or later installed

Specifications

OVERVIEW	
Application	Connect a USB computer/server to a B064- IPG Series NetDirector KVM Switch using Cat5e/6 cable, and provide it with access to Virtual Media and Common Access Card (CAC)
Model Type	Interface Modules

CONNECTIONS	
Connector A	RJ45 (FEMALE)
Connector B	HD15 (MALE)
Connector C	USB A (MALE)

Related Items

Required Products

Related Model	Description	Qty.
B064-016-02-IPG	16-Port, 2+1 User NetDirector Cat5 IP KVM Switch, TAA Compliant	1
B064-016-04-IPG	16-Port, 4+1 User NetDirector Cat5 IP KVM Switch, TAA Compliant	1
B064-032-02-IPG	32-Port, 2+1 User NetDirector Cat5 IP KVM Switch, TAA Compliant	1
B064-032-04-IPG	32-Port, 4+1 User NetDirector Cat5 IP KVM Switch, TAA Compliant	1
B064-016	KVM Switch - 16-Port NetDirector 1U Rackmount Cat5 KVM Switch	1
N001-003-GY	3-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-007-GY	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-014-GY	14-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1
N001-025-GY	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	1

Optional Products

Related Model	Description	Qty.
B055-001-PS2	KVM Switch Accessories - PS/2 Server Interface Unit for B064-Series NetDirector Cat5 KVM Switches	1
B055-001-USB	KVM Switch Accessories - USB Server Interface Unit for B064-Series NetDirector Cat5 KVM Switches	1
B055-001-USB-V2	KVM Switch Accessories - USB Server Interface Unit with Virtual Media Support for B064-Series NetDirector Cat5 KVM Switches	1
B055-001-SER	KVM Switch Accessories - Serial Server Interface Unit for B064-Series NetDirector Cat5 KVM Switches	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=4977.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.