

CS1744



- 4-Port USB Dual-View KVMP™ Switch
- CS1744 KVM Switch integrates functions of video signal dual output and USB KVM switches. It allows a computer with dual-screen support to pair with two VGA/SVGA/Multisync displays via a USB keyboard and mouse. Furthermore, CS1744 provides 1 USB port on each of the front and rear panels, allowing each server to share any USB peripheral device that is connected to this HUB.



Features

- Allows one USB keyboard, USB mouse, speakers, microphone and two displays to control four dual display computers
- 2 port USB Hub built in
- Multiplatform support: compatible with all operation platforms PC (Windows, Linux and most others), Mac and Sun
- With speaker and microphone support
- [Bi-directional switching and flexible interoperability: switch permits independent PC, independent peripheral, and independent audio function, regardless of KVM switch focus](#)
- Buzzer On/Off via hotkey
- Keyboard and mouse emulation for error free booting
- Computer selection via front panel pushbuttons and hotkeys
- Superior video quality - up to 2048 x 1536; DDC2B
- Firmware upgradeable
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX, Mac, Sun and FreeBSD
- SUN/Mac keyboard support and emulation*
 - *1.PC keyboard combinations emulate SUN/Mac keyboards.
 - *2.SUN/Mac keyboards only work with their own computers.

Specification

Computer Connections		4	
Port Selection		Hotkeys, Pushbutton	
USB Port/ Audio Port Selection		Hotkey	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White)
		Video	2 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White)
		Speaker	1 x Mini Stereo Jack Female (Green)
		Microphone	1 x Mini Stereo Jack Female (Pink)
	KVM Ports		4 x SPHD-15 Male (Yellow)
		Video1	
		Keyboard/Mouse	4 x SPHD-15 Female (Green)
		Video2	
	USB Hub		2 x USB Type A Female (White)
	F/W upgrade		1 x RJ11 Female (Black)
	Power		1 x DC Jack (Black)
Switches	Port	4 x Pushbutton	
LEDs	On Line / Selected	4 (Orange)	
	USB Link	4 (Green)	
Emulation	Keyboard/Mouse	USB	
Video		2048 x 1536; DDC2B	
Scan Interval		1~99 seconds	
Power Consumption		DC5V, 1.35W	
Environment	Operating Temp.	0~50°C	
	Storage Temp.	-20~60°C	
	Humidity	0~80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	1.03 kg	
	Dimensions (L x W x H)	27.00 x 8.70 x 5.50 cm	

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2012 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.