

### 2.5in Aluminum USB 3.0 External SATA III SSD Hard Drive Enclosure with UASP – Portable External HDD

StarTech ID: S2510BMU33



The SAT2510BMU33 USB 3.0 Hard Drive Enclosure with UASP lets you connect a 2.5in SATA III hard drive (HDD) or solid state drive (SSD) through an available USB port. The enclosure delivers optimal performance with a USB 3.0 connection, but is backward compatible with USB 2.0/1.1 host connections as well.

Enhanced with UASP (USB Attached SCSI Protocol), this 2.5" SATA III enclosure performs up to 70% faster than conventional USB 3.0 when paired with a UASP-enabled host controller. Using a more efficient protocol than the traditional USB BOT (Bulk-Only Transport), UASP reduces latency, significantly increasing transfer speeds.

With support for SATA I/II/III, and large capacity drives (tested up to 1TB) this HDD enclosure is compatible with virtually any 2.5in SATA hard drive, and greatly increase the storage/backup capabilities of your computer.

The USB 3.0/SATA III enclosure requires no external power adapter and features high quality aluminum construction, ensuring both portability and durability when carried as a laptop accessory.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

#### **Applications**

- Take advantage of new laptops and desktops with USB 3.0 (UASP) connectivity
- Create a fast, portable external storage solution for desktops, laptops or netbooks
- Upgrade from a USB 2.0 drive enclosure to faster USB 3.0
- Add extra storage to almost any USB enabled computer system
- Back up important data to an external storage device
- Share large files between computers quickly and securely without a network
- Retrieve data from old SATA drive, or turn the unused drive into additional external storage space



#### **Features**

- Compliant with USB Attached SCSI Protocol (UASP) Transport Specifications
- Compatible with SATA revision I/II/III (1.5/3.0/6.0 Gbps) drives
- Light weight and durable aluminum enclosure
- Powered directly from the USB port
- SuperSpeed USB 3.0 compliant host interface supporting data transfer rates up to 5Gbps
- High Speed USB 2.0 compliant host interface, with transfer rates up to 480Mbps
- Power/Activity LED indicator
- Plug-and-Play and Hot-Swap compatible





### **Technical Specifications**

Warranty 2 Years Interface USB 3.0

Number of Drives 1

Drive Size 2.5in

Drive Type SATA

Drive Installation Fixed

Fan(s) No

Chipset ID ASMedia - ASM1053

Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Female Host Connectors 1 - USB 3.0 Micro-B (10 pin; SuperSpeed) Female

Type and Rate USB 3.0 - 5 Gbit/s
Type and Rate SATA III (6 Gbps)

RAID No

Max Drive Capacity Currently tested with up to 1TB 5400 RPM hard drives

OS Compatibility Windows XP (32/64-bit)/ Server 2003 (32/64-bit)/ Server 2008 R2/ Vista (32/64-bit)/ 7

(32/64-bit)/ 8 (32/64-bit)

Mac OS X

Linux

Color Black

Enclosure Type Aluminum and Plastic

Max Drive Height0.4 in [9.5 mm]Product Length4.7 in [120 mm]Product Width3 in [77 mm]Product Height0.6 in [15.5 mm]Product Weight3.4 oz [97.7 g]

LED Indicators 1 - Power & Activity

Power Adapter Included USB-Powered

Operating Temperature 0°C to 40°C (32°F to 104°F)

Storage Temperature -10°C to 65°C (14°F to 149°F)

Humidity Operation Humidity: 10% ~ 90% RH

Storage Humidity: 5% ~ 95% RH

System and Cable

Requirements

Available USB port

Included in Package 1 - 2.5" USB 3.0 SATA III HDD Enclosure

Included in Package 1 - Screw Kit





# Hard-to-find made easy®

Included in Package

1 - 18" USB 3.0 Cable

Included in Package Shipping (Package) 1 - Product Manual

Weight

1 lb [0.5 kg]

## Certifications, Reports and Compatibility











