

## SDI to HDMI® Converter – 3G SDI to HDMI Adapter with SDI Loop Through Output

StarTech ID: SDI2HD



The SDI2HD 3G SDI to HDMI converter enables you to turn a 3G SDI video signal into an HDMI video output. The adapter features a built-in 3G SDI daisy chain port, giving you the ability to further extend the SDI source to up to 755ft (230m) over standard coaxial cable, for large scale HD-SDI video broadcasting distribution.

To ensure you maintain perfect high-definition video quality the SDI-HDMI converter features supports resolutions up to 1080p, allowing you to convert SDI to HDMI without sacrificing video quality.

For hassle-free installation, the SDI to HDMI converter offers a plug-and-play solution that includes pre-installed mounting brackets and requires no software or driver installation.

The SDI2HD is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Convert a 3G SDI video run to HDMI from up to 755ft (300m) away
- Connect your HDMI display to a 3G SDI video run
- Output to an HDMI Display and continue your 3G SDI run up to an additional 755ft (300m) using the daisy chain port

### Features

- Built-in 3G SDI daisy chain port
- Receives 3G SDI signals from up to 755ft (230m)
- Supports video resolutions up to 1920x1200 / 1080p
- Plug and play SDI to HDMI conversion
- Supports AES & EBU Audio Decoding
- Pre-installed Mounting brackets

**Technical Specifications**

Warranty	2 Years
Ports	1
Cabling	Coaxial
Audio	Yes
Rack-Mountable	Yes
Chipset ID	Gennum
Daisy-Chain	Yes
Output Signal	HDMI
Connector A	2 - SDI (BNC) Receptacle
Connector B	1 - HDMI (19 pin) Female
Audio Specifications	8 Channel Digital Audio @ 48 kHz
Max Distance	230 m / 755 ft
Maximum Cable Length	230 m [754.4 ft]
Maximum Data Transfer Rate	1.485 Gbps
Maximum Digital Resolutions	1080p
Supported Resolutions	1920x1080 (1080p) @ 24, 25, 30, 50 & 60 FPS 1920x1080 (1080i) @ 50 & 60 FPS 1280x720 (720p) @ 24, 25, 30, 50 & 60 FPS
Supports 525i & 625i SD D1 format	RGB or YCbCr 4:4:4 sampled YCbCr 4:2:2 or 4:2:0 sampled
Supports 8-bit or 10-bit component digital video	
Wide Screen Supported	Yes
Color	Black
Product Length	100 mm [3.9 in]
Product Width	70 mm [2.8 in]
Product Height	25 mm [1 in]
Product Weight	202 g [7.1 oz]
Input Voltage	100 ~ 240 AC
Input Current	0.5 A
Output Voltage	5 DC
Output Current	2 A
Center Tip Polarity	Positive
Plug Type	M
Operating Temperature	0°C to 40°C (32°F to 158°F)
Storage Temperature	-10°C to 60°C (14°F to 176°F)
Humidity	5% to 90 % RH (no condensation)
Shipping (Package) Weight	0.6 kg [1.4 lb]
Included in Package	1 - SDI to HDMI Adapter

Included in Package

1 - Mounting bracket assembly (attached)

Included in Package

1 - Universal Power Adapter (NA/UK/EU/)

Included in Package

1 - Instruction manual

**Certifications, Reports and Compatibility**

