

Spec Sheet

3 ft DisplayPort™ to VGA Adapter Converter Cable – DP to VGA 1920x1200 - Black

StarTech ID: DP2VGAMM3B



The DP2VGAMM3B active DisplayPort to VGA converter cable lets you connect your DisplayPort-equipped desktop or laptop directly to a nearby VGA monitor or projector, saving the expense of additional adapters while eliminating the clutter of excess cable.

Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The DP2VGAMM3B is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Applications

- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (Desktop, Laptop computer)
- Use your VGA monitor as a secondary display, connected to a DisplayPort output
- Connect a DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting

Features

- Active DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p

uk.startech.com 0800 169 0408

StarTechcom

Hard-to-find made easy*

Spec Sheet

Technical Specifications

Warranty	2 Years
Adapter Style	Cable Adapter
Audio	No
Chipset ID	ANALOGIX 9832
Converter Type	Active
Maximum Analog Resolutions	1920x1200 / 1080p (Output)
Maximum Cable Length	0.9 m [3 ft]
Maximum Digital Resolutions	1920x1200 / 1080p (Input)
Connector A	1 - DisplayPort (20 pin) Latching Male
Connector B	1 - VGA (15 pin; High Density D-Sub) Male
Cable Length	0.9 m [3 ft]
Product Height	15 mm [0.6 in]
Product Length	915 mm [36 in]
Product Weight	90 g [3.2 oz]
Product Width	40 mm [1.6 in]
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
Shipping (Package) Weight	0.1 kg [0.2 lb]
Included in Package	1 - DisplayPort™ to VGA Adapter Cable

Certifications, Reports and Compatibility









uk.startech.com 0800 169 0408