



1000Base-LX Industrial SFP Single-Mode LC Module (10km)

TI-MGBS10 (v1.0R)

- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Wide operating temperature range of -40° – 85 °C (-40° – 185 °F)
- Supports data rates of up to 1.25Gbps
- Transmission distance of up to 10km (6.2 miles)
- Low Electromagnetic Interference (EMI) design
- Supports 1310nm single-mode network transmissions
- Duplex LC optical interface
- Low power consumption
- 3-year warranty

The 1000Base-LX Industrial SFP Single-Mode LC Module, model TI-MGBS10, is designed to operate within a wide temperature range and is well suited for industrial environments. This SFP module works with standard SFP slots found on industrial switches and fiber converters. The TI-MGBS10 is compatible with Duplex LC fiber connector types and supports gigabit single-mode fiber connections at distances of up to 10 kilometers (6.2 miles).



Hot-Pluggable SFP

Hot-pluggable SFP transceiver compatible with a MSA compliant SFP slot



Fiber Wavelength

Compatible with single-mode 1310nm transmissions



Fiber Distance

Supports networking for distances up to 10km (6.2 miles)






Fiber Interface

LC-type duplex connector



Operating Temperature

Rated for an operating temperature range of -40° – 85 °C (-40° – 185 °F)



Fiber Applications

Long distance fiber networking for industrial, manufacturing, and corporate / education campus applications.

Fiber Mode / Distance

Single-Mode transceiver spans distances up to 10km (6.2 miles) and supports up to 1.25Gbps.

Compatibility

Hot-pluggable with a MSA compliant SFP slot and compatible with fiber cables with LC-type duplex connectors.

Duplex LC optical interface



Specifications

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

Device Interface

- SFP MSA Compliant
- LC duplex connector

Data Transfer Rate

- 1.25Gbps

Wavelength

- 1310nm

Optical Output Power

- -9 ~ -3 dBm

Distance

- 10km (6.2 mi.)

Special Features

- Hot pluggable
- Metal enclosure

Sensitivity

- -23 dBm

Power

- Consumption: 1W

Operating Temperature

- -40 – 85 °C (-40 – 185 °F)

Operating Humidity

- Max. 95% non-condensing

Dimensions

- 57 x 13 x 8.5 mm (2.2 x 0.5 x 0.3 in.)

Weight

- 19g (0.67 oz.)

Certifications

- CE
- FCC

Warranty

- 3-year warranty

Package Contents

- TI-MGBS10
- Quick Installation Guide