







## Technical Data Sheet

<p><b>General</b></p> <p>Article number: 6345</p> <p>Description: Colad Heavy Duty Spraymask (4 m x 150 m, 17 micron)</p>	
<p><b>Specifications</b></p> <p>Form: Film on roll. Color: White, non-transparent. Film thickness: 17 micron. Film width x length: 4 meter x 150 meter. Roll width: 100 cm. Odor: Odorless. Temperature resistance: App. 120 °C. Decomposition temperature: &gt; 300 °C. Solubility in water: Insoluble. Relative density: 910 – 990 kg/m<sup>3</sup>. Auto ignition temperature: &gt; 350 °C. Properties: Static - the film 'clings' to the surface. Extra thick. Absolutely silicone free. Specially treated for optimal paint adhesion. Can be used with infrared drying (max. 120°C).</p> <p>Packaging: Per roll in a carton box, 48 cartons boxes per pallet. Carton box can be used as a dispenser.</p>	
<p><b>Application</b></p> <p>Colad products are worked up and designed for use in car body shops. The Masking Films are ideal for quick and efficient covering of a vehicle and protect it against overspray, dirt and dust. Colad Heavy Duty Spraymask is an extra thick (17 micron), white masking film with paint adhesion - primer and/or paint adheres permanently to the film. This film has static properties, is easy to cut (art.no. 2070 or 2075) and can be used with infrared drying (max. 120°C). By using the Colad Mobile Foil Dispenser (Art.no. 2060) covering can be done by one person. Colad Heavy Duty Spraymask is environmentally friendly and can be recycled, safely incinerated or buried in the ground.</p> <p>Used for:</p> <ul style="list-style-type: none"> <li>• Sanding / Surface Preparation</li> <li>• Painting</li> </ul> <div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;">  <p>Paint adhesion</p> </div> <div style="text-align: center;">  <p>High static power</p> </div> <div style="text-align: center;">  <p>High tensile strength</p> </div> <div style="text-align: center;">  <p>Extra thick (17 micron)</p> </div> <div style="text-align: center;">  <p>Infrared drying max. 120°C</p> </div> </div> <p>The Colad assortment has a complete range of Masking Film for quick and efficient masking, together with the 6340 (3,8 m x 200 m) 6340300 (3,8 m x 300 m), 6365 (4 m x 300 m), 6375 (4 m x 150 m), 6660-5 (5 m x 120 m) and the 6660 (6 m x 100 m) there is a fitted film for every job.</p>	
<p><b>Created by :</b> E.M.M. International BV Marsweg 59 8013 PE Zwolle The Netherlands</p> <p style="text-align: right;">phone +31 38 4676600 fax +31 38 4676699 <a href="http://www.emm.com">www.emm.com</a></p>	