

Technical Data Sheet

General

Article number: 9004##
Description: Colad Aqua Dynamic Masking Tape



Specification

- Adhesive type: Rubber solvent based, absolutely free of silicones.
- Paper: Saturated water proof green crepe paper.
- Thickness: 130 micron (total).
95 micron (backing only).
- Weight: 100 g/m² (total).
61 g/m² (backing).
39 g/m² (adhesive).
- Elongation: 8%.
- Temperature resistance: 60 minutes at 130 °C.
- Tensile strength MD: 87,5 N/25 mm².
- Adhesion to steel: 4.8 N/25 mm².
- Roll lengths: 50 Meter.

Available versions:

| | Width | Rolls per box |
|------------------|---------------|---------------|
| Art. no. 900419: | 19 mm x 50 m. | 48 |
| Art. no. 900425: | 25 mm x 50 m. | 36 |
| Art. no. 900438: | 38 mm x 50 m. | 24 |
| Art. no. 900450: | 50 mm x 50 m. | 24 |

Remarks

Engineered for the professional user, suitable in high demanding situations!

Colad Aqua Dynamic Masking tape with high temperature resistance to minimize the chance of residue. This tape is especially designed for the professional user and perfectly suitable where waterborne (or 2K) systems are used.

- For water-based paint systems
- Up to 130 degrees temperature resistance for 1 hour!
- Sharp and clean edge for precise sticking and easy application
- Excellent adhesion both to rubber and metal
- Tape can be removed easily and without residue

The Colad assortment has a complete line of masking tape, together with the Classic (9075##), Premium (9070##), Ultimate (9020##) and specialty tapes like; Fineline, Foam Masking and Stegoband there is a complete line of masking tapes suitable for all types of applications.

Created by:

EMM International BV
The Netherlands



phone +31 38 4676600
www.emm.com
sales@emm.com