


## Technical Data Sheet

<p><b>General</b></p> <p>Article numbers: 901006, 901012, 901019 and 901025</p> <p>Description: Colad Acrylic Foam Tape</p>	
<p><b>Specification</b></p> <ul style="list-style-type: none"> <li>- Carrier: Polyethylene foam.</li> <li>- Density : 100 kg / m<sup>3</sup>.</li> <li>- Adhesive : Acrylic solvent base.</li> <li>- Color : Black.</li> <li>- Liner : White PE film (siliconised).</li> <li>- Total thickness : 0,8 mm (AFERA 4006).</li> <li>- Primary adhesive strength : 15 N / 25mm (Finat no. 9).</li> <li>- Peel adhesion on stainless steel : 30 N / 25mm (AFERA 4001).</li> <li>- Peel adhesion on PE : 2 N / 25mm (AFERA 4001).</li> <li>- Shear adhesion 23 °C : 2 kg / 625 mm<sup>2</sup> (AFERA 4012).</li> <li>- Temperature resistance (short) : 110 °C.</li> <li>- Service temperature : -40 to 90 °C.</li> <li>- Advised storage conditions : In original packing; at 21 °C; at rel. humidity of 50%.</li> <li>- Available widths: 6, 12, 19 and 25 mm.</li> <li>- Length per roll: 10 meter.</li> <li>- Packing: Per roll in a plastic bag.</li> </ul>	
<p><b>Remarks</b></p> <ul style="list-style-type: none"> <li>- Adheres weather strips, registration plates and accessories to cars.</li> <li>- Surface must be prepared to be dry &amp; dust free before application.</li> <li>- Good initial adhesion strength.</li> <li>- Resistance against aging.</li> <li>- UV-resistant.</li> <li>- Water resistant.</li> <li>- Petrol resistant.</li> <li>- Does not absorb water.</li> <li>- Easy application "around the corner" due to flexible liner.</li> </ul>	
<p><b>Created by :</b> E.M.M. International BV Marsweg 59 8013 PE Zwolle The Netherlands</p> <p style="text-align: right;">phone +31 38 4676600 fax +31 38 4676699 <a href="http://www.emm.com">www.emm.com</a></p>	