

First edition date: March 19, 2002 Last revision date: February 19, 2015

Number of pages: 1

Technical Data Sheet

General

Article number: 9020xx

Description: Colad Ultimate Masking Tape



Specification

- Adhesive type: Solvent based, absolutely free of silicones.- Paper: Natural white / yellow saturated crepe.

- Thickness: 135 micron (total).

90 micron (backing only).

- Weight: 98 g/m² (total).

59 g/m² (backing). 39 g/m² (adhesive).

- Temperature-resistance: 60 minutes at 110 ° C.

- Elongation: 9%.

Tensile strength: 85 N/25 mm².
 Adhesion to steel: 4,5 N/25 mm².
 Roll lengths: 50 Meter.

Available versions:

Width Rolls per box
Art. no. 902019: 19 mm. 48
Art. no. 902025: 25 mm. 36
Art. no. 902030: 30 mm. 40
Art. no. 902038: 38 mm. 24
Art. no. 902050: 50 mm. 24

Remarks

Colad Ultimate Masking tape with high temperature resistance to optimize the application of the product. This tape is especially designed for the professional car painter and for application in the car repair business.

- Up to 110 degrees for 1 hour!
- Sharp and clean edge for precise sticking and easy application
- Excellent adhesion both to rubber and metal.
- Tape can be removed easily and without residue.

The Colad assortment has a complete line of masking tape, together with the Classic (9075xx), Premium (9070xx), Aqua Dynamic (9004xx) and specialty tapes like; Fineline, Foam Masking and Stegoband there is a complete line of masking tapes suitable for all types of applications.

Related products of Colad

Article number: 6375xx

Description: Colad Breathable Spraymask

Created by:

EMM International BV

Bohemenstraat 19, 8028 SB Zwolle, The Netherlands www.emm.com



T +31(0)38 467 66 00 www.colad.co

