



Technical Data Sheet

<p>General</p> <p>Article number: 9080xx Description: Colad Foam Masking Tape</p>	
<p>Specification</p> <p>Carrier: PU-Foam (on polyester base) Density: 29.3 kg/m³ Resistance to traction: 228 KPa Adhesive: Hot-melt, block-polymer base Color: Transparent Smell: Odorless Temperature resistance (short): 180°C Advised storage conditions: In original packing, at < 35°C, at normal ventilation and no longer than 12 months. Available: 908013 – 13 mm x 50 m 908019 – 19 mm x 35 m Packing: Per roll into a dispenser box Delivery: 120 boxes per pallet</p>	
<p>Remarks</p> <p>Colad Foam Masking Tape is designed to seal the apertures of cars. It protects against sharp edges and prevents overspray from bleeding through. The foam can be easily applied and guarantees a correct isolation. Does not leave any residue upon removal. Silicon free.</p> <p>Chemical resistance of: Water – Excellent Acids and base – Good Oil and greases – Good Aliphatics – Poor Aromatics – Poor Alcohols – Good</p>	
<p>Related products of Colad</p> <p>Article number: 9090 Description: Colad Sensor Covers</p>	
<p>Created by: EMM International BV Bohemenstraat 19, 8028 SB Zwolle, The Netherlands www.emm.com</p> <div style="display: flex; justify-content: space-between; align-items: center;">  <div style="text-align: right;"> <p>T +31(0)38 467 66 00 www.colad.co</p> </div> </div>	