

Article number: 9080

Description: Diagonal Foam Masking Tape

EAN: 8714247043608



Watch now on  YouTube 

Colad Diagonal Foam Masking Tape

Seal apertures between panels preventing the need for rework on hard paint lines by using our innovative diagonally shaped Foam Tape. Easy to apply and remove without leaving any residue. Specifically designed to help you create the smoothest paint transitions possible preventing the need to rework on your panels. Save time and achieve the smoothest end-result possible. Suitable for use in the smallest apertures.

Features and benefits Colad Diagonal Foam Tape

- Innovative diagonal shape
- Easy to apply due to the dispenser box
- Designed to prevent the need for rework on hard paint lines
- Create flawless paint transitions in hard to reach places
- Eliminate hard paint lines without any effort
- Save time by preventing the need for rework
- Easy to apply and remove without leaving any residue

Packaging information

Per roll in a dispenser box, 300 boxes per pallet

Technical information

- Carrier: PU-Foam (on polyester base)
- Density: 25 kg/m³ (ISO 845) / 33 kg/m³
- Resistance to traction: 120 kPa ISO 1798 / 450 kPa ISO-1926
- Adhesive: Hot-melt, block-polymer base
- Color: Transparent
- Length: 38 m
- Temperature resistance (short): 180°C
- Advised storage conditions: In original packing, at < 35°C, at normal ventilation and no longer than 12 months.

Frequently Asked Questions

> How to mask car apertures and jambs on cars?

Colad Diagonal Foam Masking Tape is especially designed to mask car apertures, to fill up the jambs and prevents them from overspray. It protects against sharp edges and prevents overspray from bleeding through and it provides a smooth edge since the adhesion line is placed "inside" of the aperture. It's essential to mask the jambs on a vehicle before repairing it to prevent them from overspray. Colad Foam Masking Tape provides a smooth edge since the adhesion line is placed "inside" of the aperture.

> How to apply foam masking tape?

Clean the surface before applying the Foam Masking Tape. Make sure the adhesive part of the tape faces the inside of the vehicle. Don't stretch out the foam masking tape during application. Apply the tape all through the aperture/jamb for complete protection.

Related products



9080xx

Foam Masking Tape

Certifications



ISO 1798:2008



ISO 1926:2005

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.