TECHNICAL DATA SHEET

Creation date: 06-03-24

Number of pages: 3



Article number: 000452

Description: HR 1400 Spray Gun Cleaner

EAN: 8714247041437





Hamach HR 1400 Spray Gun Cleaner

Cleaning your spray gun in between jobs is a time-consuming task. The quick and compact Spray Gun Cleaner HR 1400 increases your productivity by enabling you to clean your spray gun from leftover waterborne paint in a matter of seconds! It limits your time loss and gets the highest efficiency out of your disposable cup system. It contributes to a clean and safe working environment due to its integrated and suitable cans. The cleaner is durable and easy to clean thanks to its stainless steel body. Easy to operate in just three simple steps: Jet, Flush and Dry!

Benefits of the Spray Gun Cleaner:

- · Environment-friendly: limited use of water and limited waste
- No messy cleaning with inadequate squeezing bottles
- Integrated jerry cans (no cans on the floor)
- Easy to use: Jet, Flush and Dry!
- Made from stainless steel

Packaging information

Per piece

Technical information

- Capacity jerry cans (stored in closed atmosphere with extraction) (L): 2x 2.5
- Dimensions incl. pressure regulator (LxWxH) (cm): 20 x 30 x 85
- Weight (kg): 8
- Extraction connection (mm): 80
- Housing: High quality AISI 304 stainless steel
- Earthed: Earth wire / earth by extraction tube
- Pneumatic connection: 1/4"
- Advisable working pressure (bar) (pressure regulator included): 3 4

TECHNICAL DATA SHEET

Creation date: 06-03-24 Number of pages: 3



Frequently Asked Questions

> Which tools do I need to install the Spray Gun Cleaner?

Tools you need to install the spray gun cleaner: Electric drill - ø 5 mm drill (metal wall) / ø 10 mm drill (brick/concrete wall) - Rivet gun - Ratchet + socket 10 mm - Wrench no. 13 - Level

> Can the Spray Gun Cleaner be used in ATEX zones?

Yes, the HR 1400 can be placed in ATEX zones 1 and 2. European norm: 2014/34/EU

> How do I use the Spray Gun Cleaner?

Connect your spray gun to the cleaner using the quick connector. Place the left tube in the paint cup adapter/connection. Twist the left venture valve (red) to flush water and compressed air through the spray gun to blow out left over paint quickly. Place the middle tube in the paint cup adapter and press the black button to flush out all paint residues and flush the paint channel. Clean the nozzle of the spray gun with the brush in the middle. Press the button on the right to activate the blow dry function and dry your spray gun.

> How compact is the HR 1400?

The dimensions of the Spray Gun Cleaner: 20 x 30 x 85 cm

Related products



Certifications



Atex certification

EU norm 2014/34/EU

TECHNICAL DATA SHEET

Creation date: 06-03-24

Number of pages: 3





Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.

EMM International BV Bohemenstraat 19, 8028SB Zwolle, The Netherlands +31(0)38 467 66 00 E sales@colad.com www.colad.com