

Colad Industrial Neoprene Gloves

Industrial Neoprene Gloves for multiple use

Resistant to most chemicals (frequent usage). Ridged for improved gripping. To get the best service from you gloves ensure that after use all contaminant is removed. Store in dry condition away from sunlight and heat. Before use, check the glove for any damage. Do not use a damaged glove.

Cleaning instruction:

Wash the gloves thoroughly with mild soap or a non-abrasive, low-pH detergent. Use lukewarm water and ensure all areas, including between fingers and the palm, are cleaned. Gently scrub the gloves with a soft brush or cloth to remove stubborn residues. After washing, air dry the gloves thoroughly in a clean, well-ventilated area before storing under the described conditions.

Storage:

Storage procedures are the main factor in determining glove shelf life. Gloves should be kept in their packaging protected from sunlight, artificial light, humidity and stored at temperatures between 5°C - 35°C. Storage under these conditions should provide shelf life of 5 years.

Packaging information

One pair in a plastic bag with size indication. 12 pairs in a carton.

Technical information

- Colour: Black
- Packing: One pair in a plastic bag with size indication
- Packaging Unit: 12 pairs in transport carton.
- Material: Neoprene
- Length: 330 mm
- Weight: 130 g
- Design: Non-slip fingers
- Available sizes: L and XL
- Notified body number: CE 2777
- Ongoing conformity: CE 0598



Article number: 531000x

Description: Industrial Neoprene Gloves



Art no.	Variant	EAN
5310000	L	8714247002018
5310002	XL	8714247002032

Frequently Asked Questions

> What gloves do I use for what process?

Colad offers a complete range of gloves, suitable for all steps in the paint process. We categorize three types of gloves for different steps in the paint process:

Preparation: For disassembly, assembly and preparation we provide you with the Colad Polyester Preparation Gloves. Colad Preparation Gloves offers protection against mechanical risks. The EN 388:2016+A1:2018 test indicates the abrasion, blade cut, tear and puncture resistance.

Painting: Colad disposable nitrile gloves are especially developed for use during the paint process, offering comfort and protection for the user and protection against paint contamination.

Cleaning: For cleaning with various chemicals, Colad advises to use their Industrial Nitrile or Neoprene gloves. These Gloves are fitted with a soft, anti-allergic liner that prevents allergies and strengthens the gloves. Both Colad gloves are tested according to EN ISO 374-1-:2016+A1:2018/Type A (chemical resistance), EN ISO 374-4:2019 (degradation) and EN ISO 374-5:2016 (bacteria and virus) which means they are leak-proof, protect against mechanical risks and chemical dipping (full contact).

Related products



5200xx

BodyGuard®



5000

Respirator A1P2



5085

Safety Goggles

Certifications



EU 2016/425

Personal Protective Equipment (PPE) CAT III according to European regulation (EU) 2016/425. PPE of complex design protects against risks that cause irreversible damage to health. In accordance with with EN ISO 21420:2020 Protective gloves: General requirements and test methods.



EN ISO 374-1:2016+A1:2018/Type A

AKLMNOPST
For complete test results, see manual



EN 388:2016+A1:2018

3110X
For complete test results, see manual



EN ISO 374-5:2016

Protection against bacteria and fungi: pass
Protection against viruses: pass



MANUAL

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.