

## Colad Seam Sealing Tape

A time saver for applying sealing seams for paint projects on car, truck, and camper doors and angles.

Seam Sealing Tape is a reinforced acrylic tape with high tack and shear strength performance acrylic adhesive. Excellent resistance to solvent, chemical, UV, and heat, making the tape bond securely to a very wide range of substrates. Two variants of 9 mm and 12 mm for the perfect sealing. Ideal for reviving older sealings and/or paint preparation on automotive doors and angles.

Replace old seams with new seam. Just apply the new seam on the spot, paint the object, dry the paint and ready; Time saving!

Features and benefits:

Ideal for renewing sealing seams automotive doors and angles  
Easy to use and to apply  
Immediately paintable, you don't need an adhesion promoter  
Time saving versus liquid sealers  
Excellent resistance to solvents, chemicals, UV, and heat  
Flat profile, it tacks very well to all smooth surfaces and is easy shapeable to the object  
Flexible for applying on doors and angles  
Easy removable without any residue

Application:

The product can be applied in between seams to create a permanent seal. Application on a prepared and degreased surface. Remove the liner after application so that it is immediately applicable to paint. No need to prepare the surface of the tape for the basecoat.



**Article number:** 9067xx

**Description:** Seam Sealing Tape



Art no.	Variant	EAN
906709		
906712		

## Packaging information

Per roll. 906709 per 140 rolls in outer box, 906712 per 100 rolls in outer box.

## Technical information

- Colour: white
- Roll length: 9 m
- Roll diameter (Ø) : 14 cm
- Width roll: 906709 - 9 mm 906712 - 12 mm
- Roll weight : 906709 – 100 g 906712 – 131 g
- Packaging Unit: 906709: Per roll / 140 rolls per box 906712: Per roll / 100 rolls per box
- Storage: Preferred temperature 20-25°C
- Shelf Life: One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

# TECHNICAL DATA SHEET

---

Creation date: 17-04-24      Number of pages: 3



- Carrier: Acrylic foam base in clear carrier
  - Liner: Kraft paper
  - Adhesive: High tack acrylic (solvent based)
  - Thickness: 0.5 mm and 1 mm ( $\pm 0.05$  mm)
  - Width: 9 mm and 12 mm ( $\pm 1$  mm)
  - Length: 9 m ( $\pm 0.1$  m)
  - Peel adhesion: PSTC-3 2.8 kg/25 mm
  - Shear adhesion: PSTC-7 over 72 hours with 2 kg on 25 mm x 25 mm at 25°C
  - Tensile strength: Over 50 kg/25 mm x 25 mm
  - Heat resistance: PSTC-9 over 24 hours with 1 kg on 25 mm x 25 mm at 80°C
  - Service temperature: -40°C to 170°C
  - Application temperature: : -10°C to 150°C
-

## Frequently Asked Questions

- > **Do I need an adhesion promoter before painting?**  
No, Once in place, you can start painting immediately.
  - > **How can I remove the Seam Sealing tape?**  
Just stretch the tape and you can remove it.
- 

## Related products



**53200x**

Polyester Preparation Gloves

---

### Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.