

# HCV 410 HQ

hamach  
DUTCH ENGINEERING

Art.no. 000561

The HCV 410 HQ can be connected to an electric ring line to 20 – 30 metres. Depending on the type of sanding machine, a max. of 6 extraction points can be used simultaneously. This extraction unit is equipped with a molton filter for the coarse sanding dust and a nylon filter for the finer dust. These filters are cleaned by way of a manual shaking device which should be operated four times a day to prevent clogging of the filters. A switch box with star delta switch for slow startup is supplied standard with this unit. Regulation of this unit by remote control is problematic.

- Mobile dust extraction unit
- Manual filter cleaning
- No fan belt
- Minimum maintenance
- Built-in vacuum valve and thermal safeguard
- Suitable for 2 swing arms and 4 machines



## Technical data

Volt	400 Volt
Air current	300 m <sup>3</sup> /h = 5000 ltr./min.
Under pressure	24 Kpa = 240 m. bar
Capacity	4 kW = 5,5 PK
Weight	100 kg.
Dimensions	111,5 x 62 x 96 cm (LxBxH)
Sound level	70 dBA
Filter material	Molton (059108) + Nylon bag (059138)
Filter cleaning	Manual
Tank capacity	45 Ltr.

EMM International BV  
Marsweg 59  
8013 PE Zwolle  
The Netherlands  
T +31(0)38 467 66 00  
F +31 (0)38 467 66 99  
verkoop@emm.com  
www.emm.com

More information: [www.emm.com](http://www.emm.com)

**emm**  
first in non-paint