

# HCV 510 HQ

hamach  
DUTCH ENGINEERING

Art.no. 000562

The HCV 510 HQ can be connected to an electric ring line up to 70 metres. Depending on the type of sanding machine a max. of 5 extraction points can be used simultaneously. This extraction unit is equipped with a molton filter for coarse sanding dust and a nylon filter for the finer dust. These filters are cleaned by way of a manual shaking device which should be operated at least 4 times a day to prevent the filters from clogging. A switch box with star delta switch for slow startup is supplied standard with this unit. It is also possible to regulate the HCV 510 HQ unit by remote control.

- Mobile dust extraction unit
- Manual filter cleaning
- No fan belt
- Minimum maintenance
- Built-in vacuum valve and thermal safeguard
- Suitable for 3 swing arms and 5 machines



## Technical data

Volt	400 Volt
Air current	550 m <sup>3</sup> /h = 9.166 ltr./min.
Under pressure	26 Kpa = 260 m. bar
Capacity	5,5 kW = 7,5 PK
Weight	160 kg.
Dimensions	132 x 66 x 120 cm (LxBxH)
Sound level	80 dBA
Filter material	Molton (059108) and Nylon bag (059138)
Filtercleaning	Manual

EMM International BV  
Marsweg 59  
8013 PE Zwolle  
The Netherlands  
T +31(0)38 467 66 00  
F +31 (0)38 467 66 99  
verkoop@emm.com  
www.emm.com

More information: [www.emm.com](http://www.emm.com)

**emm**  
first in non-paint