

First edition date: September 6, 2006 Last revision date: 11/1/2019

Number of pages: 1

Technical Data Sheet

General

Article number: 8144

Description: Booth Coating

Wet, non tacky application



Specification:

Deliverable: in cans of 5 L Consumption: +/-15 m² per L

Application; Spray gun, 1.3-2.5 nozzle/ 1.5-2 bar pressure
Coating Thickness Recommended at 65 micron, multiple coats possible

(to a maximum of 5)

Humidity; Recommended 40-60% RV

Packing: per box of 4 x 5 L

Shelf life: 2 years at 10-30°C unopened

Remarks

A new alternative for masking a spray booth Based on the great success of Colad Antidust! With Booth Coating is quick and easy to work Application with any type of spray gun One layer

One layer Dries quickly

Wash off with (hot) water or high pressure sprayer

- Strong film, protects the spray booth wall from overspray
- Dry coating, non-tacky
- Thinner resistant
- Instant savings in time and material
- Colad Booth Coating is non-hazardous and bio-degradable

Disclaimer

Technical Data Sheet & Material Safety Data Sheet; it is the responsibility of the user to read understands and apply the information of the TDS. The information about work and environmental safety is available on the material safety data sheet (MSDS) via www.colad.co. It is the responsibility of the user to read and apply the information.

Products are for professional use. Necessary protective equipment and clothing should be worn. The repairs should always be done in accordance with the OEM rules and specifications. All information is for the user's consideration, investigation and verification. The specific use applications and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of any of the products mentioned for the user's specific application.

Created by:

EMM International BV

Bohemenstraat 19, 8028 SB Zwolle, The Netherlands

www.emm.com



T +31(0)38 467 66 00 www.colad.co

