

Article number: 905050

Description: Surface Protection Tape

EAN: 8714247004593



Colad Surface Protection Tape

Especially developed for the protection of vehicle surfaces during sanding, grinding and light blasting jobs. Perfectly suited for the temporary wedging of glued windscreens.

Benefits of Surface Protection Tape:

- No air bubbles during application, this results in complete surface adhesion and protection
- Silicone free
- The tape can be perfectly torn both in length and width with no unraveling of the cloth
- Easy to remove and leaves no residue, even after temporary exposure to temperatures higher than 60°C

Packaging information

Per roll in a plastic bag

Technical information

- Colour: Silver
- Carrier: Laminated linen
- Length: 50 meter
- Width: 50 mm
- Thickness: 0.28 mm
- Tensile strength: 20 kgf / 25 mm
- Elongation: 10%
- Temperature resistance: 60°C

Frequently Asked Questions

> **Where do I apply Colad Surface Protection Tape?**

The tape must be applied to bumpers, moldings, spoilers and mirrors and also steel.

> **Is this product easy to remove?**

Easy to remove and leaves no residue, even after temporary exposure to temperatures higher than 60°C.

> **For which application is this product created?**

Surface Protection Tape has been especially developed for the protection of vehicle surfaces during sanding, grinding and light blasting jobs.

Related products



9005xx

Attachment Tape



9010xx

Double-faced Foam Tape

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.