

Colad Ultimate Masking Tape

A professional masking tape that is heat resistant, leaves no residue, has sharp and clean edges and an excellent adhesion to both rubber and metal. Colad Ultimate Masking tape with high temperature resistance to optimize the application of the product. This tape is especially designed for the professional car painter and for application in the car repair business.



The benefits of Colad Ultimate Masking Tape:

- Heat resistance up to 110°C for 1 hour
- Sharp and clean edges for precise sticking and easy application
- Excellent adhesion both to rubber and metal
- Tape can be removed easily and without residue

Article number: 9020xx

Description: Ultimate Masking Tape

Art no.	Variant	EAN
902019	19 mm	8714247000397
902025	25 mm	8714247000403
902038	38 mm	8714247000410
902050	50mm	8714247000427

Packaging information

19 mm x 50 m 48 rolls per box, 25 mm x 50 m 36 rolls per box, 38 mm x 50 m 24 rolls per box, 50 mm x 50 m 24 rolls per box

Technical information

- Adhesive type: Solvent based, absolutely free of silicones
- Paper: Natural white / yellow saturated crepe
- Thickness: 135 micron (total). 90 micron (backing only)
- Weight: 98 g/m² (total). 59 g/m² (backing). 39 g/m² (adhesive)
- Temperature-resistance: 60 minutes at 110 ° C
- Elongation: 9%
- Tensile strength: 85 N/25 mm² .
- Adhesion to steel: 4,5 N/25 mm²
- Roll lengths: 50 Meter

Frequently Asked Questions

> **Is this masking tape heat resistant?**

Colad Ultimate Masking Tape is heat resistant up to 110°C for 1 hour.

> **For what surfaces is this masking tape suitable?**

Colad Ultimate Masking Tape is suitable for a wide variety of surfaces, it has for instance good adhesion to steel and rubber.

> **Is this masking tape silicones free?**

Colad Ultimate Masking Tape is a solvent based adhesive that is absolutely free of silicones.

Related products



9070xx

Premium Masking Tape



6365xxx

Premium Masking Film



2060xxx

Masking Paper Premium



9090

Sensor Covers

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.