

**Article number:** 000565

**Description:** Central vacuum system HCV 7000 TQ

**EAN:** 8714254718600



Watch now on  YouTube



## Hamach Central vacuum system HCV 7000 TQ

The Hamach Central Dust Extraction system HCV 7000 TQ is designed to support a dust free working process in a 24/7 operational industrial production environment. The HCV 7000 TQ has been designed for the simultaneous connection of 7 sanding tools and can be configured to meet all your production process requirements. Choose Hamach HCV TQ series and you choose proven technology for automotive, marine and industry! Check-out the Hamach HCV references!

Dust free process results in higher efficiency. Protect employees against fine dust (from wood, metal, plastics, mastic, putty, coating) produced by sanding. Reduce defects in the paint process! And less dust in the working area resulting in higher efficiency! Work safe and efficient with Hamach HCV TQ series!

Top Quality Central Dust Extraction HCV 7000 TQ

- Middle and large size industry
- Top quality fine dust extraction
- Middle and large sized industrial use
- 24/7 operation
- Powerful up to 110 m length of tube work
- 6 M-class filters with pneumatic filter cleaning
- Durable system
- Up to 7 extraction points for simultaneous sanding:

TQ series - Warranty up till 10 years!

Standard 24 months warranty. Take a Hamach Service Contract and the warranty period\* will be extended till a maximum of 120 months!

\*Ask us for the Hamach Service Contract conditions. Choose Hamach and you choose a reliable and durable solution!

---

## Packaging information

Per piece

---

## Technical information

- Max. extraction points: 7
- Volt (V): 380 - 400
- Power (kW): 6.0 (2 x 3.0 kW)
- Air flow (m<sup>3</sup> /h): 620

- Air flow (L/min): 10.300
- Under pressure (Kpa): 26
- Under pressure (m. bar): 260
- Number of motors: 2
- Air pressure (bar): 5
- Weight (kg): 325
- Dimensions L x W x H (cm): 135 x 60 x 150
- Noise level (dBa): 72
- Polyester non woven filters m2: 6 x 0.8
- Filter surface (m<sup>2</sup>): 4.8
- Automatic filter cleaning: Yes
- Container volume (L): 50
- Tube work (m): ± 110
- Switch box (24 V): Standard
- Inverter available: Optional
- Formulated according to ATEX standards: Optional

## Related products



**000585**

Aluminum Pre-separator



**000556**

Swing Arm HSA 625 C



**000577**

Energy Box Basic 230 V



**000214**

One-Hand Orbital Sander



**TOOL**

### Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.