

Colad Premium Masking Tape

Premium masking tape with heat resistance, sharp and clean edges, excellent adhesion and no residu after removal. Colad Premium Masking tape with high temperature resistance to optimize the application of the product. This tape is especially designed for the professional car painter and for application in the car repair business.

The benefits of Colad Premium Masking Tape:

- Up to 80 degrees for 1 hour
- Sharp and clean edge for precise sticking and easy application
- Excellent adhesion both to rubber and metal
- Tape can be removed easily and without residue

Packaging information

19 mm x 50 m 48 rolls per box, 25 mm x 50 m 36 rolls per box, 30mm x 50m 40 rolls per box, 38 mm x 50 m 24 rolls per box, 50 mm x 50 m 24 rolls per box

Technical information

- Adhesive type: Natural rubber / solvent based absolutely free of silicones
- Paper quality: Semi crepe
- Paper color: Creme
- Thickness: 110 micron (total)
- Weight: 95 g/m2 (total) 57 g/m2 (backing) 38 g/m2 (adhesive)
- Temperature Resistance: 60 minutes at 80°C 30 minutes at 100°C 10 minutes at 120°C
- Roll lengths: 50 meter



Article number: 9070xx

Description: Premium Masking Tape

Art no.	Variant	EAN
907019	19 mm	8714247006719
907025	25 mm	8714247006726
907030	30 mm	8714247006733
907038	38 mm	8714247006740
907050	50 mm	8714247006757

Frequently Asked Questions

> **Is this masking tape heat resistant?**

Colad Premium Masking Tape has a heat resistance for 60 minutes at 80°C, 30 minutes at 100°C and 10 minutes at 120°C.

> **For what surfaces is this masking tape suitable?**

Colad Premium Masking Tape has a strong rubber and solvent based adhesive that makes it suitable for a lot of surfaces, for instance rubber and metal.

> **How to remove masking tape residu?**

Colad Premium Masking Tape has been created not to leave any residu after removal.

Related products



6365xxx

Premium Masking Film



2060xxx

Masking Paper Premium



9090

Sensor Covers

Disclaimer

It is the responsibility of the user to read, understand and apply the information contained in this data sheet. Products are for professional use only. Necessary protective equipment and clothing should be worn. Repairs should always be done in accordance with OEM guidelines and regulations. All information is for the user's consideration, investigation and verification. The specific use, application and conditions of use are beyond the control of EMM International BV. It is the responsibility of the user to determine the suitability of the product for the user's specific application.