

ARROW ARCHITECTURAL DOOR CONTROLS

ARROW 324VP – CAM ACTION

EASY OPENING VARIABLE POWER DOOR CLOSER WITH SLIDE RAIL



324VP fitted with Polished Chrome Flowline cover

Suitable for:

Care homes, Residential homes, Schools, Colleges, Hospitals, Clinics, Municipal buildings, Libraries, Museums, Theatres, Pubs, Clubs and Hotels.

Power size: 2–4.

Design:

Can be fitted Figure 1 and transom mounted.

Cam action door closers are high efficiency, thereby minimising the effort needed to open a door.

Individual controls for door speed and latching fitted as standard.

The closing speed can be controlled by turning the screw marked “S” on the closer body with a screw driver.

Older or more vulnerable people may benefit from a slower closing speed.

Suitable for both Left and Right hand opening.

Can be applied and fitted to the door on pull side and transom mounted on the pull side. Fixture to the door on the push side is available as an option.

Robust construction, designed and manufactured in the UK to ensure years of maintenance-free operation.

Cover finishes:

A range of stylish cover options are available, including Stainless Steel, Bright Chrome, Satin Chrome, Polished Brass, Satin Brass, Bronze, Satin Nickel, Polished Nickel and Silver Paint:

Covers are also available in painted finishes to RAL standard – details upon request.

Cover formats available: Standard and Flowline.

CE marked – Certified for fitting to fire doors.

Patented Product.

ARROW 324VP – CAM ACTION

CE	Fully CE marked to BS EN1154.
EN Classifications (Applies to Fig. 1 and Fig. 61, Pull Side)	3 8 $\frac{4}{2}$ 1 1 3
Fire Testing	Fire tested to BS EN 1634 part 1 for timber doors up to 120 minutes and steel doors up to 240 minutes.
Certifire	Certifire Approved. CF5038.

Size Range 2–4, BS EN 1154

Adjustable Power Setting	Max Door Width (mm)	Door Mass (kg)	Min Closing moment	
			4°	88° to 92°
2–4	1100	80	26	9

Body Dimensions (mm)			Standard	Flowline	Slimline
	Length 228	Cover Dimensions (mm)	Length 255	Length 258	Length 254
	Height 50		Height 65	Height 65	Height 55
	Depth 38		Depth 44	Depth 44	Depth 44

Arrow Architectural

Tything Road, Arden Forest Industrial Estate, Alcester, Warwickshire B49 6ES United Kingdom.

Tel: +44 (0) 1789 762 575 Fax: +44 (0) 1789 762 673

email: info@arrow-architectural.com



Manufactured in the United Kingdom.

In keeping with our policy of continuous improvement, we reserve the right to vary without notice any technical specification stated.

WWW.ARROW-ARCHITECTURAL.COM