

CE4F-E | Electromagnetic door closer



Hold-open or free-swing
in a single stylish closer

Trusted by **Professionals**

UNION

ASSA ABLOY

Experience a safer
and more open world

The CE4F-E is a flexible electromagnetic door closer offering both hold open and free-swing functionality in one stylish unit.

Easy door opening is guaranteed with electromagnetic door closers. They are ideal for high traffic applications or where doors are frequently used by children, the elderly or the less able.


To comply with BS EN 1155 standards, UNION's CE4F-E closers are connected to the building's fire or smoke alarm system. When activated, this allows the closer to re-engage and shut the door to prevent fire and smoke from spreading.



- Easy to fit
- CE marked
- Certifire tested to FD120 for timber doors
- Certifire tested to FD240 for steel doors*
- Fixed power size 4
- Suitable for fitting in figure 1 and figure 66, without affecting the power size
- Detachable loop, enabling electrics and installation to be completed separately
- Increased loop length for flexibility when installing
- Efficient cam and roller mechanism for ease of use
- 2 year guarantee

Feature	CE4F-E
CE	BS EN 1155
Power size	4
Maximum door width	1100mm
Maximum door weight	80kg
Action	Cam & roller
Fitting	Fig 1, Fig 66
Certifire	Yes
Suitable for timber fire doors	FD120
Suitable for steel fire doors	FD240*
Power adjustment	No
Adjustable closing speed	Yes
Adjustable latching speed	Yes
Backcheck	No
Delayed action	No
Angle of opening	170°
Non-handed	Yes
Power supply required	24V DC
Guarantee	2 years

*FD240 for insulated steel fire doors



Finishes

Silver as standard, other finishes on request including SSS

Ideal applications

Residential living, nurseries, schools, care homes, hospitals, specialised disability facilities