

## **Super Lock Bolt** **Data Sheet**



### **Features:**

- Highly developed 10 pin radial tumbler lock insert.
- Lock bolt diameter 25.4mm (1 inch) case hardened to 60 rockwell hardness (746 VPN), crop, drill and saw resistant.
- Anti drill centre pin on radial pin tumbler lock.
- Drill resistant lock cover to prevent hollow core drilling of lock.
- 10mm diameter steel ball bearings operated by internal cam mechanism.
- Lock face design is resistant to attack by slide hammer (dent puller) devices.
- Bulldog Super Lock Bolt has been used in many applications of security products that have passed independent attack test including TNO Road Vehicle Research Institute, TUV and Sold Secure.
- Resistant to attack by punches or drifts due to internal lock chamber design.
- Keys can only be removed in locked position, no possibility of accidental locking.
- 2 keys supplied with lock as standard. Multiple locks can be supplied with same key for fleet or multi user applications.

### **Bulldog Security Products Ltd**

Units 2,3,4 Stretton Road, Much Wenlock, Shropshire, TF13 6DH.

Tel: 01952 728171 Fax: 01952 728117

email: [sales@bulldogsecure.com](mailto:sales@bulldogsecure.com) [www.bulldogsecure.com](http://www.bulldogsecure.com)