



5500 Series

Cylinder lockcases

A comprehensive range of mortice lockcases for use with Euro profile cylinders.

Briton 5520 Cylinder Sashlock



Certification

- CE Marked
- DIN 18251 compatible
- EN 12209 compliant
- Fire tested to EN 1634 for use on fire doors up to 90mins timber / 4hr steel
- DoP available at www.britoninspec.co.uk

Features & Functions

- Powder coated steel case.
- Backset 60mm - Centres 72/78mm
- Grade 316 stainless steel single piece forend. Optional square ended forend is also available.
- Quick reversible latch allows quick and trouble free on-site handing without the need to dismantle the lockcase.
- Profiled latch and forend provides very positive location and a smooth, quiet operation.
- Chrome plated steel latch.
- Cast follower with phosphor bronze bushes reduces wear of follower during extended use.
- 8mm follower is designed to grip the spindle to eliminate unwanted tolerance between components.
- 30° follower action with springing suitable for high frequency applications.
- Positive follower angle (1°) reduces the effect of wear which can lead to lever droop.
- Drill resistant heavy duty hardened deadbolt with 22mm throw on a single turn of the cylinder.
- Chrome plated steel bolt.
- Bolt through fixing holes to DIN 18251
- Sleeved fixing holes assist in bolt location, provide added strength to the lockcase and help prevent mechanical failure due to ingress of foreign objects.

Briton

5500 Series

Cylinder lockcases

Product ref.	Function/description	Centres	CE Classification
5510	Deadlock - cylinder operates deadbolt only	72mm	3X810G4BA00
5520	Sashlock - lever operation of latchbolt, cylinder operation of deadbolt. Cylinder to latch function.	72mm	3X810G4BA20
5530	Bathroom lock - lever operation of latchbolt, 8mm bathroom turn follower to operate deadbolt	78mm	3X810G-B020
5535	Bathroom deadbolt - 8mm bathroom turn follower to operate deadbolt only	n/a	3X810G-B000
5540	Latch - lever operation of latchbolt only	n/a	3X810G-B020
5550	Nightlatch - lever operation from inside to withdraw the latchbolt, cylinder from outside. Hold-back function.	72mm	not CE marked
5555	Nightlatch - lever operation from inside to withdraw the latchbolt, cylinder from outside. No hold-back function.	72mm	3X8100G-B020
5560	Escape sashlock - lever operation of latchbolt, cylinder operation of deadbolt from either side. Inside lever withdraws latchbolt and deadbolt simultaneously for immediate escape. (This is not a split follower lock and must be used with a double cylinder)	72mm	3X810G4BA20 (EN 12209) 376B1442AB/D (EN179)

Radiused and square forends are available with matching strikes. Add suffix .R or .S to product code: e.g 5510.R for radiused forend and strike, 5510.S for square forend and strike.

