


BEYOND SECURITY



Simplex® 3000




Model 3001



- Combination Entry
- Key Override (not supplied)
- Passage
- Lockout

Model 3002



- Combination Entry
- Key Override (not supplied)
- Cylinder Guard
- Passage
- Lockout

Features

Access Control

Mechanical pushbutton lock eliminates problems and costs associated with issuing, controlling, and collecting keys and cards. Provides exterior access by combination.

No Battery

Fully mechanical lock eliminates the material and labor expense of battery replacements

Locking Device

Adams Rite 4510/4710/4910 mortise latch

Number of Codes

Single access code—one easy-to-manage code for all users

Programming

Lock is easily programmed via keypad without removing lock from the door

Handing

Non-handed; required drive assembly is factory-handed, not field reversible

Key Override

Accepts Maximum Security (MS) mortise cylinders; can be used to override the lock combination and gain access using a key. Allows facilities to initiate or maintain a master-keyed security system (keyed alike or keyed differently).

Operation Modes

Pushbutton Access

Passage—allows access without using the lock entry code. Feature activated from the outside using cylinder override key.

Lockout—disables the lock so that entry code cannot be used to gain access. Access is permitted using the key override only. This is activated from the outside using the cylinder override key.

Economical

A cost effective access control solution

Mechanical Features

<i>Construction</i>	All metal cast front housing, force-resistant, clutch-protected fixed thumbturn
<i>Numeric Keypad</i>	Vandal resistant, solid metal pushbuttons
<i>Finishes</i>	Satin Chrome 26D (626); 55 (695) Duranodic
<i>Stile Width</i>	1 ⁷ / ₈ " (48 mm) minimum, required for mounting
<i>Latch</i>	Purchased separately (Adams Rite)
<i>Backset</i>	Model 3010: Right Hand; Right Hand Reverse— ³¹ / ₃₂ " (25 mm) Model 3020: Left Hand; Left Hand Reverse— ³¹ / ₃₂ " (25 mm) Model 3030: Right Hand; Right Hand Reverse—1 ¹ / ₈ " (29 mm) or 1 ¹ / ₂ " (38 mm) Model 3040: Left Hand; Left Hand Reverse—1 ¹ / ₈ " (29 mm) or 1 ¹ / ₂ " (38 mm)
<i>Strike</i>	Sold separately (Adams Rite or Kaba Ilco Corp.)
<i>Weight</i>	4 lbs. (1.8 kg)

Installation

<i>Door Thickness</i>	1 ³ / ₄ " (44 mm) maximum
<i>Items Supplied Include</i>	Installation instructions, full-scale template, combination change key, and screwdriver

Certification and Testing

<i>Durability</i>	Weather resistant
-------------------	-------------------

Warranty

<i>Warranty</i>	1-year warranty
-----------------	-----------------

