



Never compromise on quality!



COVER-IT CARPET PROTECTOR

Self-Adhesive Protection Material For Carpets and Textile Surfaces

Description

A high performance, self-adhesive protection material for covering and protecting synthetic carpets and textiles against against mess, dirt, spillages and staining, etc. whilst painting and decorating, plastering, tiling and general building and maintenance projects.

Uses

- Low tack, temporary, self-adhesive, waterproof carpet protective film.
- For use on synthetic carpets and other textiles.
- Easy application, simply unwind, roll and **COVER-IT**.
- Waterproof
- Safer to use than loose dust sheets and coverings heavy duty
- Tear resistant can be used in at temperatures between +15°C to +25°C.

Application

Perform a compatibility test on an inconspicuous area prior to full application. Ensure the surface is free from dust, moisture and grease before application.

Place the roll onto the floor with the open end facing away from the direction it is to be applied. Unpeel approx 300mm (12") of the protective cover and press it to the surface firmly by hand. Push the roll away from you making sure it follows a straight line, smoothing it out as it unwinds to eliminate air bubbles or creases. Ensure film is safely and securely positioned before commencing work.

Limitations

- **DO NOT** use on long pile/ wool carpets
- In rare circumstances, **COVER-IT** can leave sticky residues on certain surfaces so it is recommended test areas be carried out prior to application.
- Replace **COVER-IT** after 4 weeks. Any unexpected residue can be easily removed by hand or with Bond It Multi-Wipes - dependant on surface, check the compatibility of any fabric dyes with the wipes in an inconspicuous area first.
- Check textiles carefully before application - any textiles with lightly held fibres or fringes may detach when the film is removed the user should inspect textiles for any potential weak points before application.

- Do not use underfloor heating whilst **COVER-IT** is in position or 24 hours prior to application.
- In heavily trafficked areas or if exposed to excessive light or heat, replace at least once a week, checking for any residues left on the carpet
- Carpets newly laid using adhesive will require 72 hours for the vapours to dissipate before application of **COVER-IT** film.
- **COVER-IT** will not adhere to damp or wet textiles. Recently cleaned carpets and uncured concrete floors: after film application moisture vapour is prevented from escaping and may cause discolouration of carpet fibres.
- Disposable - singular use only.
- Not suitable for hard surfaces, rugs or loose carpet tiles.
- Slippery when wet.

Removal

Easy and simple - the low tack adhesive will allow for easy removal. Lift each edge in turn and pull back towards the middle to keep any contaminants central on the roll ensuring any spills are covered and cannot escape before lifting the whole sheet.

Storage Conditions

Store in cool dry conditions between 5 and 25°C. Safe in normal use however as a precaution keep polythene outer packaging away from children.

Shelf Life

12 months from date of manufacture.

Disposal of Containers

Dispose of in accordance with local regulations – sheet is polythene. Container is cardboard - widely recycled locally. Make care when removing from textiles with loosely held fibres or fringes

Safe Handling Precautions

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Adhesive	pressure sensitive acrylic
Thickness	< 50 microns

Container Sizes

Code:	BDCICP25	BDCICP50
Size:	600mm x 25M	600mm x 50M
Colour:	Clear	Clear
Barcode:	5060021369499	5060021369857

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 20/03/17
Supersedes: V2 03/09/14

