

Mini Magnets

10001/2

- Operating voltage: 12 or 24Vdc
- Aluminium
- Current draw: 500mA at 12Vdc
250mA at 24Vdc (*at temperature 20°C*)
- Magnetic bond sensor monitor output remotely monitors the door lock or unlock status. (*N.C. Output-Door opened; N.O. Output-door closed*) (*SPDT rated 3A at 12Vdc*),
- Status LED lights
- Operating temperature: -10 to 55°C (*14 to 131°F*)
- Humidity: 0 to 95% non-condensing
- Lock's surface temperature: Current temperature $\pm 20\%$ (*when power is on*)
- Holding force: Up to 600lbs (272kg)
- Weight: 2.0kg (*approx*)



VARIATIONS

10001	Mini Magnet
10001DS	Mini Magnet C/W Door Status
10002	Monitored Mini Magnet
10002DS	Monitored Mini Magnet C/W Door Status

DIMENSIONS

	LENGTH	WIDTH	DEPTH
Magnet	250	42	26
Armature Plate	185	38	12

All dimensions in mm



ICS Security Solutions Ltd - Your Security Solutions Partner

Units 1-2 JBJ Business Park Northampton Road Blisworth Northampton NN7 3DW
Telephone: 01604 858565 Facsimile: 01604 859545 Email: orderline@icssecurity.co.uk

