

# LM215 Series

## 21.5" LED Monitors



LM215 & LM215C

### Key Features

- Versatile Connectivity (BNC In/Out, S-Video, VGA, HDMI, Audio In/Out) - LM215C Model Only
- Built-In Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction
- Fast Response Time (5ms)
- Audio Input, Internal Speakers, VESA Compatible
- On-Screen Display Menu
- Desk Stand (Detachable)
- Selectable Signal Source
- VESA Standard Wall Mount

## Technical Specification

Model Number	LM215	LM215C
Resolution	1920 (H) x 1080 (V)	
Active Display Area	476.64 (W) x 268.11 (H) mm	
Pixel Pitch	0.2482 x 0.2482 mm	
Contrast Ratio	1000:1	
Brightness	200 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
Response Time	5ms	
Viewing Angle	Up/Down: 160°, Left/Right: 170°	
Backlight Life	40,000 Hours	
Compatibility	PC Compatible	
Display Colours	16.7 Million	
Speaker	Multimedia Speaker	
Number of Speaker	8Ω, 2W x2	
3D Comb Filter	N/A	Yes
Mute	N/A	Yes
Connector	HDMI x 1, VGA x1, DVI x1	HDMI x1, VGA x1, BNC x2 In, BNC x1
Audio Interface	Audio In x1	Audio in x1, Audio Out x1
Power Interface	AC In x1	
OSD	Yes	
Certification	CE / ROHS / UL	
Power Supply	Built-In	
Power Consumption	<30W in ON Mode	<35W in ON Mode
Voltage	100V - 240V, AC60/50Hz	
Work Humidity	20% - 70%	
Work Temperature	-10°C to 50°C	
VESA	Yes (100 x 100 mm)	
Dimensions ( W x H x D)	516.5 x 376 x 185 mm	
Weight	3.8 kg	

Features and specifications are subject to change for further improvement without any notice

www.geniecctv.com  
 sales@geniecctv.com  
 T: +44 (0) 1707 330 541  
 F: +44 (0) 1707 330 543

Genie CCTV Ltd.  
 CCTV House, City Park,  
 Watchmead,  
 Welwyn Garden City,  
 Hertfordshire,  
 AL7 1LT,  
 United Kingdom