

Digital wireless monitoring set



Digital wireless monitoring set

TVAC18000

Complete set with recorder, 2 x wireless outdoor cameras, 3 x power supply units and accessories

- ✓ Simple step-by-step installation with app and QR code (iOS, Android)
- ✓ App access of up to 4 cameras
- ✓ Recording on max. 32 GB micro-SD card (accessory) or max. 2 TB external hard disk drive via USB port
- ✓ Up to three months of continuous recording with 500 GB external hard disk drive (accessory)
- ✓ Sturdy, weatherproof outdoor cameras (IP66)
- ✓ Professional integrated motion detection (PIR sensor) with alarm function
- ✓ VGA resolution and infrared night vision function
- ✓ Low network load thanks to compressed data transfer (H.264 compression)

Digital wireless monitoring set

TVAC18000

Complete set with recorder, 2 x wireless outdoor cameras, 3 x power supply units and accessories

The compact digital wireless monitoring set from ABUS reliably protects small properties day and night: The VGA resolution makes for brilliant picture sharpness which is guaranteed even in darkness due to the integrated infrared night vision function. Sensitive motion detection identifies movement in the detection field of the camera and sets off an alarm in the event of unauthorised access. Using the app, you can access the video images of up to four cameras simultaneously and see if everything is okay.

Digital wireless monitoring set

TVAC18000

Intuitive installation with app and QR code for iOS and Android

The wireless monitoring set is also installed using the app and a QR code. You do not need any experience of CCTV systems to set up the video surveillance kit quickly and easily. Since all components communicate wirelessly, the system can be installed with almost no mess.

Digital wireless monitoring set



TVAC18000

Up to 3 months of continuous recording thanks to low network load

The efficient H.264 data compression reduces the data volume of the image data to a minimum, thereby enabling one to three months of continuous recording when connected to an external 500 GB hard disk drive. Recording is done either on a micro SD card or via a USB port on an external hard disk drive with a maximum of 2 TB. All storage media are available as accessories and can be integrated into the wireless monitoring set according to your preferences.

Digital wireless monitoring set

TVAC18000



Wireless outdoor camera

TVAC18010

Wireless outdoor camera for digital wireless monitoring set

- ✓ Simple step-by-step installation with app and QR code (iOS, Android)
- ✓ App access of up to 4 cameras
- ✓ VGA resolution and infrared night vision function
- ✓ Sturdy, weatherproof outdoor cameras (IP66)
- ✓ Professional integrated motion detection (PIR sensor) with alarm function

Wireless outdoor camera

TVAC18010

Sturdy wireless outdoor camera for 24 h safety



This wireless outdoor camera serves as an extension of the digital wireless monitoring set from ABUS. Thanks to the solid, weatherproof design, it is ideal for outdoor areas. The VGA resolution and the infrared night view function ensure optimal video image data quality at any time of day or night. Integrated motion detection with an alarm function reliably detects movement and sets off an alarm if there is danger of unauthorised access.

Intuitive installation with app or QR code

Installation is done step-by-step using the app or the QR code, making it easy even for technical laymen. The app also allows access to up to four cameras of this type, making practical mobile monitoring possible.

Wireless outdoor camera

TVAC18010



Scope of delivery set

TVAC18000

Packaging with flap

- ✓ 1 x Recorder incl. antenna
- ✓ 2 x Camera incl. antenna and bracket
- ✓ 3 x Power supply
- ✓ 1 x Quick Guide
- ✓ 1 x User manual
- ✓ 1 x 8 GB micro SD card
- ✓ 1 x HDMI cable
- ✓ 1 x LAN cable
- ✓ 1 x mouse
- ✓ mounting material

A Version

- ✓ DE, GB, FR, NL IT

B Version

- ✓ DK, GB, PL, ES, RU, SWE

C Version

- ✓ US, FR, ES, PT

Scope of delivery camera

TVAC18010

Packaging with flap

- ✓ 1 x Camera incl. antenna and bracket
- ✓ 1 x Power supply
- ✓ 1 x User manual
- ✓ mounting material

A Version

- ✓ DE, GB, FR, NL IT

B Version

- ✓ DK, GB, PL, ES, RU, SWE

C Version

- ✓ US, FR, ES, PT



GUI & App



Specifications

Transmission parameters

| | |
|-----------------------------|----------------------------|
| Method | Radio Signal |
| Modulation | FHSS: PSK |
| Bandwidth | 6 Mbps (RF, RJ45 Ethernet) |
| Effective data Speed | 4 MBps (RF, RJ45 Ethernet) |
| Effective Wireless Distance | max. 500 ft. (clear view) |

Specifications

Video/Audio parameters

Video Resolution

VGA: 640x480; CIF: 352x288

Frame Rate

Single camera: VGA/CIF up to 30 FPS

Multiple camera: VGA @ 15 fps, CIF @ 30 fps

Audio Video Compression

H.264

Viewing Options

(Monitor) Full Screen / Quad / S-Quad

Specifications

Recorder parameters

| | |
|---------------------|--|
| Storage Media | SD Card, Flash drive, HDD |
| Length of Recording | VGA 25FPS: 10MB/minute |
| Motion Detection | By SW or PIR algorism, High PIR / Low PIR / PIR OFF, Individual setting for each camera |
| Motion Sensitivity | (4 steps) |
| Motion zone | 8 x 6 grid |
| Event list | Access monitor SD storage, files sort by perpetual calendar (month view) |
| Record file format | AVI |
| Storage capacity | External Hard drive (not included), max 2TB; SD card: max. 32GB |
| Recording options | manual REC, Motion REC , Schedule REC |
| Playback | QUAD / Smart QUAD / playback single camera full screen playback |

Specifications

Camera parameters

| | |
|------------------------|----------------------------------|
| Sensor | 1/4" CMOS |
| Resolution | Full VGA, 640*480 |
| Lens | 3.6 mm |
| PIR Sensor | Horizontal; 70° ; 5 m |
| View Angle | Horizontal: 60; Vertical: 44° |
| Number of LEDs | 6 IR Power-LEDs, IR CUT Switcher |
| Night Visibility | 20 ft. (8 m) |
| Power Requirements | DC 5V1A, camera: 6 ft. cable |
| Weatherproof (Ingress) | IP66 |

Specifications

General parameters

| | |
|-----------------------|---|
| Language | English, French, Spanish, German, Dutch, Dansk, Italian, Russian, Swedish, Polish |
| Power Requirements | 12 V DC / 2A |
| Operating Temperature | -10° C - +50° C |