

Double Mini Magnet

10004/5

- Operating voltage: 12 or 24Vdc
- Brushed aluminium
- Current draw: 500mA at 12Vdc x 2
250mA at 24Vdc x 2
(at temperature 20°C)
- Magnetic bond sensor monitor output remotely monitors the door lock or unlock status. (N.C. Output-Door opened; N.O. Output-door closed)
(SPDT rated 0.25A at 12Vdc)
- Operating temperature:
-10 to 55°C (14 to 131°F)
- Humidity: 0 to 95% non-condensing
- Lock's surface temperature:
Current temperature $\pm 20\%$
(when power is on)
- Holding force: Up to 600lbs x 2 (272 x 2kg)
- Weight: 4.0kg (approx)



VARIATIONS	
10004	Double Mini Magnet
10004DS	Double Mini Magnet C/W Door Status
10005	Monitored Double Mini Magnet
10005DS	Monitored Double Mini Magnet C/W Door Status

DIMENSIONS	LENGTH	WIDTH	DEPTH
Magnet	500	42	26
Armature Plate	185	38	12

All dimensions in mm



ICS Security Solutions Ltd - Your Security Solutions Partner

Units 1-2 JBJ Business Park Northampton Road Blisworth Northampton NN7 3DW
Telephone: 01604 858565 Facsimile: 01604 859545 Email: orderline@icssecurity.co.uk

