

# Standard Magnets

## 10010/20

- Operating Voltage: 12 or 24Vdc
- Aluminium
- Current draw: 500mA at 12Vdc  
250mA at 24Vdc (at temperature 20°C)
- Magnetic bond sensor monitor output remotely monitors the door lock or unlock status. (N.C. Output-Door opened; N.O. Output-door closed) (SPDT rated 3A at 12Vdc)
- Status LED lights
- Operating temperature: -10 to 55°C (14 to 131°F)
- Humidity: 0 to 95% non-condensing
- Lock's surface temperature: Current temperature  $\pm 20\%$  (when power is on)
- Holding force: Up to 1200lbs (545kg)
- Weight: 5.0kg (approx)



VARIATIONS	
10010	Standard Magnet
10010DS	Standard Magnet C/W Door Status
10020	Monitored Mini Magnet
10020DS	Monitored Mini Magnet C/W Door Status

DIMENSIONS	LENGTH	WIDTH	DEPTH
Magnet	266	68	40
Armature Plate	185	62	16
Mounting Plate	266	40	5

All dimensions in mm



**ICS Security Solutions Ltd - Your Security Solutions Partner**

Units 1-2 JBJ Business Park Northampton Road Blisworth Northampton NN7 3DW  
Telephone: 01604 858565 Facsimile: 01604 859545 Email: [orderline@icssecurity.co.uk](mailto:orderline@icssecurity.co.uk)

