

ARROW ARCHITECTURAL

DOOR CONTROLS

ARROW 325VP

MULTI-APPLICATION CLOSER WITH VARIABLE POWER ADJUSTMENT



325VP fitted with Polished Chrome Flowline cover

Suitable for:

Care homes, Residential Homes, Apartments, Schools, Colleges, Hospitals, Clinics, Municipal Buildings, Libraries, Museums, Theatres, Pubs, Restaurants, Clubs and Hotels.

Power size: Variable Power size 2–5, capable of opening to 167°.

Design:

Door speed adjustment and latching speed adjustment fitted as standard.

A range of stylish cover options are available, including Stainless Steel, Bright Chrome, Satin Chrome, Polished Brass, Satin Brass, Bronze, Satin Nickel, Polished Nickel.

Cover finishes:

Covers are also available in painted finishes to RAL standard – details upon request.

Cover formats available: Standard, Flowline.

Suitable for Both Left and Right hand opening.

Supplied with Uni-Pack (adjustable) arms and brackets; Ensures the door closer will meet all configurations, using a projection arm.

Optional Backcheck available.

Certifire tested.

Robust construction, designed and manufactured in the UK to ensure years of maintenance-free operation.

CE marked – Certified for fitting to fire doors.

Patented Product.

ARROW 325VP

Options		Certified for fitting to fire doors
325VP	Standard door closer, power size 2–5, Variable Power.	✓
325VP/BC	Standard door closer, power size 2–4, Variable Power, with Backcheck.	✓

Applications	EN Classifications
Fig. 1	3 8 $\frac{2}{5}$ 1 1 3
Parallel Arm Fig. 6	3 8 $\frac{1}{3}$ 1 1 3
Transom Fig. 61	3 8 $\frac{1}{5}$ 1 1 3

CE	Fully CE marked to BS EN1154.
Fire Testing	Fire tested to BS EN 1634 part 1 for timber doors up to 120 minutes and steel doors up to 240 minutes.
Certifire	Certifire Approved. CF277.

Adjustable Power Setting	Max Door Width (mm)	Door Mass (kg)	Min Closing moment	
			4°	88° to 92°
2	850	40	13	4
3	950	60	18	6
4	1100	80	26	9
5	1250	100	37	12

Body Dimensions (mm)		Cover Dimensions (mm)	Standard	Flowline
	Length 228		Length 255	Length 258
	Height 51		Height 65	Height 65
	Depth 40		Depth 44	Depth 44

Arrow Architectural

Tything Road, Arden Forest Industrial Estate, Alcester, Warwickshire B49 6ES United Kingdom.

Tel: +44 (0) 1789 762 575 Fax: +44 (0) 1789 762 673

email: info@arrow-architectural.com



Manufactured in the United Kingdom.

In keeping with our policy of continuous improvement, we reserve the right to vary without notice any technical specification stated.

WWW.ARROW-ARCHITECTURAL.COM