

ATEN PE1324 VERTICAL ZeroU PDU 24 PORT IP-READY



DESCRIPTION

The ATEN PE1324 Energy PDU contains 24 AC outlets and is available in IEC socket configurations.

The ATEN PE1324 Energy PDU features a space-saving Zero U design that allows it to be mounted vertically on the outside of a rack, resulting in a more efficient use of space in the server room, while providing 24 AC outlets.

The ATEN PE1324 Energy PDU should be integrated into an installation with the EC1000 Energy Box, allowing you to monitor the real-time current and environmental conditions of the Energy PDU from the front panel of the EC1000 at the rack, or via Web GUI remotely, making your server room efficiently green with ease.

Specifications :

- Power Outlets Direct : 24 x IEC C13
- Connectors Inlet : 1 x IEC 60309 32A
- Energy Sensor Port : 2 x RJ-45 Female
- Nominal Input Power : 100-240V~, 50/60Hz, 32A(Max)
- Nominal Output Power : 100-240V~, 50/60Hz Per bank 16A (Max) - Total : 32A(Max)
- Physical Properties : Housing Metal - 3.47 kg
- Dimensions : 1340 x 44 x 44 mm

Package Contents

- 1x PE1324 Energy PDU
- (Fixed power cable 150 cm - IEC 60309 - 32A power plug)
- 1x Mounting Kit
- 1x User Instructions

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : PE1324G-AX

Caractéristiques :

Certification : CE, C-Tick, TUV-CB, GOST

AC input frequency : 50 - 60 Hz

AC outlet types : C13 coupler

AC outlets quantity : 24 AC outlet(s)
Cable length : 1.6 m
Depth : 1300 mm
Ethernet LAN (RJ-45) ports : 1
Height : 44 mm
Housing material : Metal
Load capacity : 7360 VA
Manual : Y
Master (outer) case gross weight : 5.68 kg
Master (outer) case height : 166 mm
Master (outer) case length : 1465 mm
Master (outer) case net weight : 3.73 kg
Master (outer) case width : 205 mm
Maximum current : 32 A
Nominal input voltage : 100-240 V
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 1465 mm
Package height : 166 mm
Package weight : 5.53 kg
Package width : 205 mm
PDU types : Metered
Power plug : IEC 60309
Product colour : Black
Products per master (outer) case : 1 pc(s)
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Weight : 3.73 kg
Width : 40.4 mm