

HANWHA-Camera LNV-6072R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : LNV-6072R

Représentation / réalisation :

Type : IP security camera

Active tampering alarm : Y

Alert notification type : E-mail

Angle of rotation : 355°

Anti-flicker : Y

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Camera pan control : Y

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Closest focusing distance : 0.5 m

Compatible memory cards : MicroSD (TransFlash), MicroSDHC

Day/night mode : Y

Detect distance (tele) : 128.8 m

Detect distance (wide) : 27.4 m

Diameter : 13.8 cm

Dynamic range : 120 dB

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flash memory : 256 MB

Flip & mirror : Y

Focal length range : 3.2 - 10 mm

Focus : Manual
Form factor : Dome
Frame rate : 30 fps
Height : 106.1 mm
Housing material : Plastic
HTTPS encryption : Y
Identify distance : 0.5 m
Identify distance (tele) : 12.9 m
Identify distance (wide) : 2.7 m
IK code : IK10
Infrared (IR) cut-off filter : Y
Internal memory : 512 MB
International Protection (IP) code : IP66
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED type : IR
Lens viewing angle, diagonal : 132°
Lens viewing angle, horizontal : 109°
Lens viewing angle, vertical : 57.4°
Mac operating systems supported : Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Maximum aperture number : 2
Maximum memory card size : 32 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.03 lx
Mirror : Y
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1984 x 1105 pixels
Number of languages : 15
Number of lenses : 1
Number of sensors : 1
Number of users : 6 user(s)
Observe distance (tele) : 51.5 m
Observe distance (wide) : 11 m
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 350°
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 6.4 W
Power consumption (typical) : 5 W
Power source type : PoE
Privacy masking : Y
Product colour : White
Progressive scan : Y
Protection features : Dust resistant, Splash proof
Quality of Service (QoS) support : Y
Recognize distance (tele) : 25.8 m
Recognize distance (wide) : 5.5 m

Remote viewing : Y
Security algorithms : 802.1x RADIUS, EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -30 - 55 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
Tilt angle range : 0 - 67°
Total megapixels : 2 MP
Video compression formats : H.264, M-JPEG
Video formats supported : H.264, M-JPEG
Video motion detection : Y
Video streaming : Y
Web browser : Y
Weight : 525 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 137.8 mm
Wi