

HANWHA IP camera XND-L6080R



DESCRIPTION

XND-L6080R

2M Network IR Dome Camera

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XND-L6080R
Représentation / réalisation :
Type : IP security camera
Active tampering alarm : Y
Alert notification type : E-mail
Angle of rotation : 355°
Anti-flicker : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Camera pan control : Y
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Camera tilt control : Y
Card reader integrated : Y
Closest focusing distance : 0.5 m
Compatible memory cards : SD, SDHC, SDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Depth : 140.8 mm
Digital zoom : 24x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1

Flip & mirror : Y
Focal length range : 3.2 - 10 mm
Focus : Motorized/Manual
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Height : 113 mm
Highlight Compensation (HLC) : Y
Housing material : Plastic
IK code : IK08
Image quality adjustment : Contrast
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Defocus
IP address filtering : Y
LED type : IR
Lens viewing angle, diagonal : 132°
Lens viewing angle, horizontal : 109°
Lens viewing angle, vertical : 57.4°
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 2.9
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.3 lx
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : N
Night vision distance : 20 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1109 pixels
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 3.1x
Pan range : 0 - 354°
Placement supported : Indoor & outdoor
Power consumption (Power over Ethernet (PoE)) : 8 W
Power consumption (typical) : 4 W
Power source type : PoE
Privacy masking : Y
Product colour : Black, Ivory
Progressive scan : Y
PTZ control : Y
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Y
Security algorithms : 802.1x RADIUS, EAP-TLS
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -50 - 60 °C

Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
Text caption overlay : Y
Tilt angle range : 0 - 67°
Total megapixels : 2.16 MP
USB port : Y
Video compression formats : AVC, H.264, H.265, M-JPEG, MPEG4
Video motion detection : Y
Video streaming : Y
Weight : 580 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Width : 140.8 mm
Windows operating systems supported : Windows 10, Windows 7, Windows 8.1
Zoom capability : Y