

# Hanwha HCP-6320HA



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

|                                       |  |
|---------------------------------------|--|
| Brand : HANWHA                        |  |
| Part number : HCP-6320HA              |  |
| <b>Représentation / réalisation :</b> |  |
| Type : CCTV security camera           |  |
| <b>Réseau :</b>                       |  |
| Bluetooth : N                         |  |
| <b>Système d'objectif :</b>           |  |
| Auto focus : Y                        |  |
| AC input voltage : 24 V               |  |
| Alarm input/output : Y                |  |
| Back Light Compensation (BLC) : Y     |  |
| Built-in HDD : N                      |  |
| Camera pan control : Y                |  |
| Camera shutter speed : 2 - 1/12000 s  |  |
| Camera shutter type : Electronic      |  |
| Camera tilt control : Y               |  |
| Closest focusing distance : 1.4 m     |  |
| Connectivity technology : Wired       |  |
| Day/night mode : Y                    |  |
| Diameter : 22 cm                      |  |
| Digital zoom : 16x                    |  |
| Ethernet LAN : N                      |  |
| Flip & mirror : Y                     |  |
| Focal length range : 4.44-142.6 mm    |  |
| Form factor : Dome                    |  |
| Frame rate : 30 fps                   |  |
| Height : 293.6 mm                     |  |

|                                                                              |
|------------------------------------------------------------------------------|
| Housing material : Metal, Plastic                                            |
| IK code : IK10                                                               |
| Image stabilizer : Y                                                         |
| Infrared (IR) cut-off filter : Y                                             |
| International Protection (IP) code : IP66                                    |
| Lens viewing angle, horizontal : 62.8°                                       |
| Lens viewing angle, vertical : 36.8°                                         |
| Maximum aperture number : 4.4                                                |
| Maximum resolution : 1920 x 1080 pixels                                      |
| Minimum aperture number : 1.6                                                |
| Minimum illumination : 0.01 lx                                               |
| Mounting type : Ceiling/wall                                                 |
| Noise reduction : Y                                                          |
| Number of cameras : 1                                                        |
| Number of effective pixels (H x V) : 1944 x 1104 pixels                      |
| Number of lenses : 1                                                         |
| Number of sensors : 1                                                        |
| Operating relative humidity (H-H) : 0 - 90%                                  |
| Operating temperature (T-T) : -50 - 55 °C                                    |
| Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)                               |
| Pan preset speed : 700 °/sec                                                 |
| Pan range : 0 - 360°                                                         |
| Pan speed : 200 °/sec                                                        |
| Placement supported : Outdoor                                                |
| Power consumption (max) : 65 W                                               |
| Power source type : AC                                                       |
| Privacy masking : Y                                                          |
| Product colour : Ivory                                                       |
| Progressive scan : Y                                                         |
| PTZ control : Y                                                              |
| RS-485 ports : 1                                                             |
| Sensor type : CMOS                                                           |
| Storage relative humidity (H-H) : 0 - 90%                                    |
| Storage temperature (T-T) : -50 - 60 °C                                      |
| Tilt angle range : -15 - 195°                                                |
| Tilt speed : 200 °/sec                                                       |
| Total megapixels : 2.38 MP                                                   |
| Video motion detection : Y                                                   |
| Weight : 3.3 kg                                                              |
| White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp |
| Wide Dynamic Range (WDR) : Y                                                 |
| Wi-Fi : N                                                                    |
| Zoom capability : Y                                                          |