

SONY- Signage screen FWD-65X80H/T1



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : SONY
Part number : FWD-65X80H/T1
Représentation / réalisation :
HDCP : Y
AC input frequency : 50/60 Hz
AC input voltage : 220 - 240 V
Ambient light sensor : Y
Audio formats supported : FLAC, LPCM, MP3, MP4, WAV, WMA
Bezel width (bottom) : 1.85 cm
Bezel width (side) : 1.5 cm
Bezel width (top) : 1.5 cm
Built-in processor : Y
Built-in speaker(s) : Y
Composite video in : 1
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1200:1
Depth : 340 mm
Depth (with stand) : 340 mm
Digital signal format system : DVB-C, DVB-S, DVB-S2, DVB-T, DVB-T2
Display brightness : 560 cd/m ²
Display diagonal : 163.8 cm (64.5»)
Display diagonal (metric) : 164 cm
Display resolution : 3840 x 2160 pixels
Display technology : IPS
DVI port : N
Energy efficiency scale : A+++ to D
Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1
Google applications : Google Chromecast
HD type : 4K Ultra HD
HDCP version : 2.3
HDMI input ports quantity : 4
HDMI ports quantity : 4
Height : 841 mm
Height (with stand) : 905 mm
Image formats supported : JPEG
Internal storage capacity : 16 GB
LED backlighting type : Direct-LED
Native aspect ratio : 16:9
Number of built-in speakers : 2
Operating hours (hours/days) : 18/7
Operating system installed : Android 9.0
Package weight : 30 kg
Panel mounting interface : 300 x 300 mm
Placement supported : Indoor
Power consumption (standby) : 0.5 W
Power consumption (typical) : 137 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Response time : 8 ms
RMS rated power : 20 W
USB port : Y
USB ports quantity : 2
VESA mounting : Y
Video formats supported : 3GPP, ASF, AVC, AVCHD, AVI, HEVC, MKV, MOV, MP4, MPEG1, MPEG2, MPEG2-PS, MPEG2-TS, MPEG4, VC-1, VP8, WEBM, WMV, XAVC, XVID
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight : 21.7 kg
Weight (with stand) : 22.6 kg
Width : 1462 mm
Width (with stand) : 1462 mm
Wi-Fi : Y