

Eaton 9PX 3000i RT3U HotSwap IEC



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9PX3000IRTBP

Design :

Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC /RCM / KC / Energy Star

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 7 AC outlet(s)

Automatic battery test : Y

Battery technology : Sealed Lead Acid (VRLA)

Bundled software : Intelligent Power Software suite

Depth : 485 mm

Display type : LCD

Efficiency : 94%

Form factor : Rackmount/Tower

Harmonized System (HS) code : 85078000

Height : 130 mm

Hot-swap battery : Y

Input frequency : 40/70 Hz

Input operation voltage (max) : 276 V

Input operation voltage (min) : 176 V

LED indicators : Y

Management card included : N

Noise level : 40 dB

Nominal input voltage : 230 V

Nominal output voltage : 230 V

Number of input phases : 1

Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz

Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 3000 W
Output power capacity : 3 kVA
Power factor : 1
Power plug : C20 coupler
Product colour : Black
Rack capacity : 3U
Rack mount kit : Y
RS-232 ports : 1
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Sustainability certificates : ENERGY STAR
Typical backup time at half load : 9.5 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 27.4 kg
Width : 440 mm