

BENQ MH733



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BENQ

Part number : 9H.JGT77.1HE

Réseau :

Smart TV : N

Vidéo :

Full HD : Y

3D : N

AC (power) in : Y

AC input frequency : 50/60 Hz

AC input voltage : 100 - 240 V

Analog signal format system : NTSC, PAL, SECAM

Aperture range (F-F) : 2.59 - 2.87

Batteries included : Y

Built-in display : N

Built-in speaker(s) : Y

Cable lock slot : Y

Cable lock slot type : Kensington

Cables included : AC, VGA

Card reader integrated : N

Contrast ratio (typical) : 16000:1

Depth : 221 mm

DVI port : N

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Focal length range : 16.88 - 21.88 mm

Focus : Manual

HDMI connector type : Full-size

HDMI ports quantity : 2
Height : 120 mm
Horizontal scan range : 15 - 102 kHz
Keystone correction, horizontal : -20 - 20°
Keystone correction, vertical : -30 - 30°
Lamp power : 240 W
Lamps quantity : 1 lamp(s)
Light source type : Lamp
Manual : Y
Market positioning : Bussines
Matrix type : DMD
Mobile High-Definition Link (MHL) : Y
Native aspect ratio : 16:9
Noise level : 33 dB
Noise level (economic mode) : 29 dB
Number of built-in speakers : 1
Number of colours : 1.073 billion colours
Number of OSD languages : 30
Offset : 105%
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
PC Audio in : Y
PC Audio out : Y
Placement : Desktop, Ceiling
Power consumption (economy mode) : 240 W
Power consumption (max) : 355 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 320 W
Power source : AC
Product colour : White
Product type : Standard throw projector
Projection technology : DLP
Projector brightness : 4000 ANSI lumens
Projector native resolution : 1080p (1920x1080)
Remote control included : Y
RMS rated power : 10 W
Screen size compatibility : 762 - 7620 mm (30 - 300»)
Serial interface type : RS-232
Service life of light source : 4000 h
Service life of light source (economic mode) : 8000 h
Storage relative humidity (H-H) : 10 - 90%
Storage temperature (T-T) : -20 - 60 °C
Supported graphics resolutions : 640 x 480 (VGA), 1920 x 1080 (HD 1080)
Supported video modes : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Throw ratio : 1.15 - 1.5
USB 2.0 ports quantity : 2
Vertical scan range : 23 - 120 Hz
VGA (D-Sub) ports quantity : 2
Weight : 2.5 kg
Width : 296 mm

Wi-Fi : N

Zoom capability : Y

Zoom ratio : 1.3:1

Zoom type : Manual